

# DUCK ROASTER



## Features


- A**  Hanging ring  
Located at perfect height for easy handling of the ducks during cooking process
- B**  Thermometer  
Allows precise manipulation of the flame level
- C**  Insulated body  
(For all double layers model)  
Mild steel inner layer to enhance the cooking efficiency and prevent overheat body structure
- D**  Manual rotary wheels  
Mounted at the top of the roaster cover for hanging full height pig roasting  
(For CDR-10S only)

- ▶ Lava rock stand
- ▶ Ventilation hole at the cover for heat exhaust

## Duck Roaster

### 32" Single Layer


CDR-8S



Dimension	Ø810 x 1400 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN20
Oil Overflow Pipe	Ø22
Burner Ratings	16kW
Capacity	6 - 7 pieces duck

### 36" Single Layer


CDR-9S



Dimension	Ø910 x 1500 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN20
Oil Overflow Pipe	Ø22
Burner Ratings	16kW
Capacity	8 - 9 pieces duck

### 32" Double Layer


CDR-8D



Dimension	Ø810 x 1400 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN20
Oil Overflow Pipe	Ø22
Burner Ratings	16kW
Capacity	6 - 7 pieces duck

### 36" Double Layer

CDR-9D




Dimension	Ø910 x 1500 mm H
Fuel	NG: DN20 ; LPG: DN20 ; TG: DN20
Oil Overflow Pipe	Ø22
Burner Ratings	16kW
Capacity	8 - 9 pieces duck

## Full Height Pig / Duck Roaster

### 39" Double Layer

CDR-10S



Dimension	Ø1000 x 1900 mm H
Fuel	NG: DN25 ; LPG: DN25 ; TG: DN25
Oil Overflow Pipe	Ø22
Burner Ratings	28kW
Capacity	10 - 11 pieces duck or 3 - 4 pieces pig

\* All Specifications are subjected to change without prior notice.