



B-SERIES

[UPRIGHT UNIT]

Upright refrigerator / freezer



STANDARD FEATURES

- Insulation** Polyurethane foam injected under 500 tons of pressure to ensure uniformity and high structural strength.
- Finish** Tough, hygienic construction, exterior bodies are stainless steel no.4 finish. Interior is of 430 grade stainless steel BA finish. Zincalume steel top, base and back.
- Door** Choices of stainless steel full door or half door. Self closing door with easily replaceable magnetic gasket. Mullion heater standard for freezer but option for refrigerator.
- Refrigerator system** Self-contained, top mounted condensing unit. Fitted with condensate evaporator, no drain connection required.
- Controller** Multi-function microprocessor controlled with digital thermometer display.
- Model Variations**
 - Full doors
 - Half doors
 - Double pane glass door.
- Shelves** Completed with 4 pcs. PVC coated wire shelves per full door. GN pans can fit on PVC wire shelves
- Refrigerant**
 - R-134a For chiller
 - R-404a For freezer
- Other features**
 - Knock-down system, economical to transport and can be assembled on site.
 - New recessed evaporator coil design, resulting in more storage room.
 - Coved stainless steel floor pan.
 - Interior light with automatic door switch.
 - Heavy duty, adjustable, stainless steel bullet feet.
 - Left hinge or right hinge selectable.

TECHNICAL DATA	Refrigerated Models				Freezer Models			
Model number	BR 21-1D	BR 21-2d	BR 46-2D	BR46-4d	BF21-1D	BF21-2d	BF46-2D	BF46-4d
Dimension L x D x H (mm.)	680 x 830 x 2030		1320 x 830 x 2030		680 x 830 x 2030		1320 x 830 x 2030	
Capacity Cu. Ft.	18		40		18		40	
Temperature range	2°C to 5°C				-18°C to -20°C			
Cooling capacity (Btu.)	1306		2518		1661		3057	
Compressor	1/3		1/2		3/4		1	
Shelves (PVC coated)	4		8		4		8	
Door facia heater (Watts)	40	62	40 x 2	62 x 2	54	93	54 x 2	93 x 2
Defrosting system	Circulated air				Electric			
Power supply	220-240 V / 50 Hz / 1 Ph (60 Hz models are available.)							

