

[UPRIGHT UNIT]

V.2

QF-SERIES

Quick freezer

QF46-4D

with optional cylinder locks



High Quality Quick Freezer unit


STANDARD FEATURES

Insulation	Polyurethane foam injected under 500 tons of pressure to ensure uniformity and high structural strength.
Finish	Tough, hygienic construction, exterior bodies are stainless steel 304 no.4 finish. Door frame and mullion are of 430 grade stainless steel for magnetic gaskets. Interior is stainless steel 304 2B finish. Zincalume steel top, base and back.
Door	Choices of full door or half door stainless steel or full door or half door double pane 3 mm. heat reflective insulated glass. Self closing door with easily replaceable magnetic gasket. Mullion heater standard for freezer units but option for refrigerator.
Refrigerator system	Self-contained, easily removable, top mounted condensing unit. Fitted with condensate evaporator, no drain connection required.
Controller	Multi-function microprocessor controlled with digital thermometer display.
Refrigerant	• R404a for freezer
Shelves / GN pan	Complete with 4 pcs. PVC coated wire shelves per full door. Stainless steel angle slide, suit GN 2/1 pan size.
Other features	Coved stainless steel floor pan. Interior light. Heavy duty, adjustable, stainless steel bullet feet. Left hinge or right hinge selectable.
Optional extra	<ul style="list-style-type: none"> • Stainless steel wire shelves. • Stainless steel base and back. • Mullion heater for refrigerator. • Double pane heat reflective glass door. • Remote condensing unit. • Locking plate or cylinder locks. • Swivel castors.


TECHNICAL DATA

Freezer models


Model number	QF21	QF46	QF72
Dimension - L x D x H (mm.)	680 x 880 x 2095	1140 x 880 x 2095	1975 x 880 x 2095
Capacity Cu.Ft / Litres	18/510	40/1133	61/1727
Temperature range	-20 °C to -25 °C		
Cooling capacity (Btu.)	2252	4565	5432
Compressor (Hp.)	1	1-1/2	2
Shelves	4	8	12
Mullion heater (full/half doors)	82	82 x 2	82 x 3
Defrosting system	Electric		
Power supply	220-240 V / 50 Hz / 1 Ph. (60 Hz models are available.)		




QF21-1D




QF21-2D




QF46-2D




QF46-4d



QF72-3D



QF72-6d



Cross Section

