KOLDTECH[®]

STANDARD ITEMS

DISPLAY UNIT



SQRCD SERIES Square Showcase Unit

STANDARD FEATURES

Refrigerator system

Uniquely designed with cold air floating beneath each shelf. Very little air movement, therefore extending shelf life without drying out the product. Reliable self contained, bottom mounted, system, designed for tropical climate and easy servicing, Using R-404a as refrigerant. Drainage connection not necessary, as system uses condensate evaportor.

Controller

Multi-function microprocessor controlled with digital temperature display to monitor and control cabinet temperature and other functions.

Body and furnishing

- ° Stainless steel base and top.
- ° Polyurethane foamed-in-place insulated bottom panels (40 mm.)
- ° Double glazed heat reflective front and side glasses to provide grand outlook.
- ° Self closing rear sliding doors with mirror finish and fluorescent light fixtures to emphasize and increase product visibility.

Shelves

Two non adjustable stainless steel shelves and shelf supports.


Other features

78 mm high swivel casters.

TECHNICAL DATA	REFRIGERATED MODELS				
MODEL NUMBER	SQRCD-9	SQRCD-12	SQRCD-15	SQRCD-18	SQRCD - 20
Dimension L x D x H (mm.)	900 x 729 x 1358	1200 x 729 x 1358	1500 x 729 x 1358	1800 x 729 x 1358	2000 x 729 x 1358
Temperature range	2°C to 8°C				
Cabinet capacity Cu.Ft./ Litres	18.3	18.5/525	23.8/673	29/820	32.4/918
Compressor (Hp.)	1/6	1/3	1/3	1/2	1/2
Display light (w)	18 x 3	30 x 3	36 x 3	58 x 3	58 x 3
Power supply	220 V / 50 Hz / 1 Ph. (60 Hz models are available.)				



Low velocity chilled air to chill without excessive drying




FRONT VIEW: SQRCD-9



FRONT VIEW: SQRCD-12




FRONT VIEW: SQRCD-15




CROSS SECTION



Warm air to provide visibility, minimizing condensation.



FRONT VIEW: SQRCD-18



FRONT VIEW: SQRCD-20



