

GEARED MOTOR CNHM / CHHM TYPE




Fig 1. Type CNHM (0.5-2 HP)
(Grease Lubrication)




Fig 2. Type CNHM
(Grease Lubrication)




Fig 3. Type CHHM
(Oil Lubrication)

FRAME SIZE	A	C	D	E	F	G	M	N	P	Q	R	V	d	SLOW SPEED SHAFT							H	DM	J	L	Weight (kg)	FIG
														d1	L1	d1	HT	ST	MT	d1						
CNHM5-608 □	129	90	134	75	120	52	99	144	12	12	13	37	9	22h6 9/0.013	35	6	6	3.5	M6	16	214.9	147.6	140	328	14	1
CNHM5-609 □	142	100	150	90	150	60	135	180	15	15	12	40	11	28h6 9/0.013	35	8	7	4	M8	20	249.9	147.6	145	345	18	1
CNHM1-610 □	156	100	150	90	150	60	135	180	15	15	12	40	11	28h6 9/0.013	35	8	7	4	M8	20	262.9	161.6	145	391	24	1
CNHM2-610 □	170	120	162	90	150	70	135	180	15	15	12	45	11	32h6 9/0.016	45	10	8	5	M8	20	215.3	183.6	158	426	31	1
CNHM3-611 □	186	120	162	90	150	70	135	180	15	15	12	45	11	32h6 9/0.016	45	10	8	5	M8	20	250.8	207	170	487	37	2
CNHM3-612 □	186	120	204	115	190	82	155	230	20	20	15	55	14	38h6 9/0.018	55	10	8	5	M8	20	250.8	183.6	158	456	42	1
CNHM5-612 □	186	120	204	115	190	82	155	230	20	20	15	55	14	38h6 9/0.018	55	10	8	5	M8	20	252.8	228	182	513	57	2
CHHM3-613 □	240	150	230	145	290	100	195	330	25	25	22	65	18	50h6 9/0.016	70	14	9	5.5	M10	18	293.8	207	170	857	66	3
CHHM5-613 □	240	150	230	145	290	100	195	330	25	25	22	65	18	50h6 9/0.016	70	14	9	5.5	M10	18	295.8	228	182	868	76	3
CHHM5-613 □	240	150	230	145	290	100	195	330	25	25	22	65	18	50h6 9/0.016	70	14	9	5.5	M10	18	304	266	210	617	92	3
CHHM5-614 □	260	150	230	145	290	120	195	330	25	25	22	65	18	50h6 9/0.016	90	14	9	5.5	M10	18	305.8	228	182	888	79	3
CHHM5-614 □	260	150	230	145	290	120	195	330	25	25	22	65	18	50h6 9/0.016	90	14	9	5.5	M10	18	314	266	210	637	85	3
CHHM10-614 □	308	160	300	150	370	139	238	410	44	20	25	75	18	60h6 9/0.019	90	18	11	7	M10	18	314	266	210	637	95	3
CHHM5-616 □	308	160	300	150	370	139	238	410	44	20	25	75	18	60h6 9/0.019	90	18	11	7	M10	18	348.5	266	210	685	120	3
CHHM10-616 □	352	200	340	275	380	125	335	430	30	25	30	80	22	70h6 9/0.019	90	20	12	7.5	M12	24	348.5	266	210	685	129	3
CHHM10-617 □	352	200	340	275	380	125	335	430	30	25	30	80	22	70h6 9/0.019	90	20	12	7.5	M12	24	403	266	210	729	169	3

GEARED MOTOR CNVM / CVVM TYPE




Fig 4. Type CNVM (0.5-2 HP)
(Grease Lubrication)




Fig 5. Type CNVM
(Grease Lubrication)




Fig 6. Type CVVM
(Oil Lubrication)




Fig 7. Type CVVM
(Oil Lubrication with circulating pump)

FRAME SIZE	CF	D1	D2	D3	M	E	P	N	d	H	X	Y	SLOW SPEED SHAFT							DM	J	L	Weight (kg)	FIG
													d1	L1	d1	HT	ST	MT	d1					
CNVM5-608 □	94	160	134	110	48	9	3	4	11	-	-	-	22h6 9/0.013	35	6	6	3.5	M6	16	147.6	138	297	15	4
CNVM5-609 □	94	160	134	110	48	9	3	4	11	107	-	-	28h6 9/0.013	35	8	7	4	M8	20	147.6	138	297	15	4
CNVM1-610 □	108	160	134	110	48	9	3	4	11	107	-	-	28h6 9/0.013	35	8	7	4	M8	20	161.6	144	343	19	4
CNVM2-610 □	112	210	180	140	58	11	4	6	11	116	-	-	32h6 9/0.016	45	10	8	5	M8	20	183.6	156	378	25	4
CNVM3-611 □	117	210	180	140	58	11	4	6	11	137	-	-	38h6 9/0.018	55	10	8	5	M8	20	207	169	418	30	5
CNVM5-612 □	117	210	180	140	69	13	4	6	11	137	-	-	38h6 9/0.018	55	10	8	5	M8	20	183.6	156	387	28	4
CNVM5-612 □	117	210	180	140	69	13	4	6	11	137	-	-	38h6 9/0.018	55	10	8	5	M8	20	228	180	444	36	5
CVVM3-613 □	164	260	230	200	76	15	4	6	11	-	152	233	50h6 9/0.016	61	14	9	5.5	M10	18	207	169	488	64	6
CVVM5-613 □	164	260	230	200	76	15	4	6	11	-	152	233	50h6 9/0.016	61	14	9	5.5	M10	18	228	180	492	68	6
CVVM5-613 □	164	260	230	200	76	15	4	6	11	-	152	233	50h6 9/0.016	61	14	9	5.5	M10	18	266	213	541	78	6
CVVM10-613 □	164	260	230	200	76	15	4	6	11	-	152	233	50h6 9/0.016	61	14	9	5.5	M10	18	266	213	541	85	6
CVVM5-614 □	164	260	230	200	96	15	4	6	11	-	152	233	50h6 9/0.016	81	14	9	5.5	M10	18	228	180	492	72	6
CVVM10-614 □	219	340	310	270	89	20	4	6	11	-	217	200	60h6 9/0.019	80	18	11	7	M10	18	266	213	541	89	6
CVVM5-616 □	258	400	360	316	94	22	5	8	14	-	222	225	70h6 9/0.019	84	20	12	7.5	M12	24	266	213	596	107	7
CVVM10-617 □	258	400	360	316	94	22	5	8	14	-	222	225	70h6 9/0.019	84	20	12	7.5	M12	24	266	213	596	113	7
CVVM10-617 □	258	400	360	316	94	22	5	8	14	-	222	225	70h6 9/0.019	84	20	12	7.5	M12	24	266	213	640	155	7