



RESEARCH ENERGY OF OHIO

Spec Sheet - Model: BO199.9-1

Model No.:	BO199.9-1
No. of Circuits:	1
Range:	0-199.9 ohms
Accuracy:	+/- 0.1 ohm
Max Test Current:	3 milliamperes
Weight:	8 oz. (0.2 kg.)
Size:	4.1 x 1.3 x 3.6 in.
Power Source:	9 volt Alkaline Battery



FEATURES:

- Digital read-out 0 to 199.9 ohms in 0.1 ohm increments
- Automatic turn-on and shut-off.
- Low battery indication.
- Laborsaving fast connections for quick hole-to-hole or circuit analysis.
- Rugged water and corrosion resistant nylon (BO199.9-1 and BO1999-1)
- Environmentally sealed to operate in most weather.
- Safety yellow is easy to spot by equipment operators.
- Easy-to-follow instructions provided on the unit.
- Fast battery change using standard ALKALINE battery.
- Heavy duty bare terminals accept wires, banana plugs, clips or spade terminals.

OPERATION:

When using the BO199.9-1 Blaster's Ohmmeter, connect the blasting circuit to the terminals. The ohmmeter turns on automatically. The display indicates the resistance of the blasting circuit. "1---" will be displayed if the resistance exceeds the full scale range of the ohmmeter. The ohmmeter turns off automatically when disconnected. Replace the battery when BAT appears on the display.

BATTERY LIFE:

Low battery drain provides a battery life of more than 2000 hours of operation.