

CERTIFICATE OF COMPLIANCE

Certificate Number 20190429-E304648
Report Reference E304648-20131209
Issue Date 2019-APRIL-29

Issued to: TERMINAL LUGS CO LTD
110/6 Moo 2 Krungnont-Jongthanom Rd
Mahasawat, Bangkruiy, Nonthaburi 11130 THAILAND

**This certificate confirms that
representative samples of**

WIRE CONNECTORS AND SOLDERING LUGS
See Addendum Page.

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

UL 486A-486B, Wire Connectors
See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190429-E304648
Report Reference E304648-20131209
Issue Date 2019-APRIL-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL – Non-insulated crimp on terminal connectors, One Hole, Series HTS, HRS, HOS;

Cat. No. H, followed by TS, RS or OS, followed by blank, followed by 10 or 16, followed by -6 or -8.

Cat. No. H, followed by TS, RS or OS, followed by blank, followed by 25 or 35, followed by -6, -8 or -10.

Cat. No. H, followed by TS, RS or OS, followed by blank, followed by 50, 70 or 95, followed by -8, -10 or -12.

Cat. No. H, followed by TS, RS or OS, followed by blank, followed by 120, followed by -10, -12 or -14.

Cat. No. H, followed by TS, RS or OS, followed by blank, followed by 150, followed by -12, -14 or -16, followed by blank, followed by CV185.

Cat. No. H, followed by TS, RS or OS, followed by blank, followed by 185, 240, 300, 400 or 500, followed by -12, -14 or -16.

USL – Non-insulated crimp on terminal connectors, Two Hole, Series HTL, HRL, HOL;

Cat. No. H, followed by TL, RL or OL, followed by blank, followed by 10 or 16, followed by -6 or -8.

Cat. No. H, followed by TL, RL or OL, followed by blank, followed by 25 or 35, followed by -6, -8 or -10.

Cat. No. H, followed by TL, RL or OL, followed by blank, followed by 50, 70 or 95, followed by -8, -10 or -12.

Cat. No. H, followed by TL, RL or OL, followed by blank, followed by 120, followed by -10, -12 or -14.

Cat. No. H, followed by TL, RL or OL, followed by blank, followed by 150, followed by -12, -14 or -16, followed by blank, followed by CV185.

Cat. No. H, followed by TL, RL or OL, followed by blank, followed by 185, 240, 300, 400 or 500, followed by -12, -14 or -16.

USL – Non-insulated crimp on terminal splices, Series CSL, HTSL;

Cat. No. CSL or HTSL, followed by blank, followed by 10, 16, 25, 35, 50, 70, 95, 120, 185, 240, 300, 400 or 500.

Cat. No. CSL or HTSL, followed by blank, followed by 150, followed by blank, followed by CV185.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

