

TCT THAI CENTER TRANSFORMER CO.,LTD SPECIFICSTION THREE PHASE TRANSFORMER

Address: 67 / 1 Moo. 7 T. Bangkam A. Maung Nakonpathom 73000

Tel . 081 - 8054856, 034 - 219036 Fax 034 - 984092 http://www.thaicentertransformer.com e - mail : thaicenter671@hotmail.com

Transformer Specification

Quote. Ref: Customer: Project:

| Rated power | | KVA | 250 |
|-------------------------------------|-----------------------|------|--------------------------------------|
| Type of transformer | | - | Oil immersed (Hermetically sealed) |
| Standard | | - | IEC 76 |
| Cooling System | | - | ONAN |
| No. Of phase | | - | 3 |
| Frequency | | Hz | 50 |
| Rate of voltage : Primary | | V. | 33000 |
| : | Secondary | V. | 400/230 |
| Vector group | | - | Dyn 11 |
| Tapping Type | | - | Off circuit tap changer |
| | of steps | - | 5 |
| Perc | entage of tapping | - | <u>+</u> 2 x 2.5 % |
| Impedance voltage at 75 C | | % | 4 |
| NO - Load current | | % | 1 |
| Ambient temperature | | C | 40 |
| Average Temperature rise of winding | | C | 65 |
| Average Temperature rise of top oil | | C | 60 |
| Noise level not more than | | dB | 56 |
| No - Load loss | | Watt | 500 |
| Load loss at 75 C | | Watt | 2950 |
| | : 25 % of rate power | % | 98.94 |
| Efficiency | : 50 % of rate power | % | 98.08 |
| at P.F. = 1 | : 75 % of rate power | % | 98.79 |
| | : 100 % of rate power | % | 98.56 |
| Voltage regulation | : at P.F. $= 0.8$ | % | 3.22 |
| | : at P.F. $= 0.9$ | % | 2.71 |
| | : at P.F. $= 1$. | % | 1.17 |
| Impulse Withstand | : Primary winding | KV. | 125 |
| Voltage | : Secondary winding | KV. | - |
| Power Frequency | : Primary winding | KV. | 50 |
| | : Secondary winding | KV. | 3 |
| Terminal arrangement H.V. Side | | | Cable |
| | L.V. Side | | Cable |
| Installation on | | | Pole mounted / Plantform |

TCT THAI CENTER TRANSFORMER CO.,LTD SPECIFICSTION THREE PHASE TRANSFORMER

Address: 67 / 1 Moo. 7 T. Bangkam A. Maung Nakonpathom 73000

Tel . 081 - 8054856, 034 - 219036 Fax 034 - 984092 http://www.thaicentertransformer.com e - mail : thaicenter671@hotmail.com

Transformer Specification

Quote. Ref:
Customer:
Project:

| Rated power | 250 |
|--|--------------------------------------|
| Type of transformer | Oil immersed (Hermetically sealed) |
| Accessories | |
| H.V. Bushing with terminal connector | Included |
| L.V. Bushing with terminal connector | Included |
| Grounding pad or earth terminal | Included |
| upper fillter press sampling valve | Included |
| Oil drain, filter press sampling valve | Included |
| Name plate | Included |
| Arcing Horn | Included |
| Skid Base | Included |
| Mechanical pressure relief device | Included (without contact) |
| Oil level indicator | Included (with contact) |
| | Included (with contact) |
| | Included (with contact) |
| | |
| Testing | |
| - Routine test | |
| Ratio test at each position of tap | Included |
| Polarity and phase relation test | Included |
| Resistance measurement | Included |
| No - Load loss and exciting current test | Included |
| Impedance and load loss test | Included |
| Applied potential test | Included |
| Induced potential test | Included |
| Insulation resistance test | Included |
| Oil test | Included |
| - Specia test | |
| Impulse withstand test | Included (Thaicenter lab) |
| Temperature rise test | Included (Thaicenter lab) |
| | |
| | |