

Multiswitches

CASCADABLE MULTISWITCHESES

SKU : SWI8508PLUS



5-INPUT CASCADABLE PLUS Series
5-input cascadable multiswitches with active SAT and terrestrial and separate adjustment,

Main Specifications

- TV Gain adjustment
- 2 gain adjustments for High band and Low band
- High insulation &45dB'
- Low insertion loss
- High output level to cover high cable length &100m with 6,7mm coax'
- Return path included
- Low power consumption thanks to automatic check of the satellite remote feeding,
- Standard colour coding for an easy installation

Name		SWI8508PLUS
Code		271055
Inputs		4 SAT, 1 TV
Taps		8
SAT		
Bandwidth	MHz	950-2150
Positive slope gain	dB	0\6
Gain adjustment	dB	15
Maximum output level (-35dBc 2 toni)	dBμ	110
Insertion loss	dB	-1.5
SAT-SAT insulation	dB	>45

Name		SWI8508PLUS	
TV			
Bandwidth	MHz	85-862	
Positive slope gain	dB	-4/0	
Gain adjustment	dB	20	
Maximum output level (-35dBc 2 toni)	dBμ	107	
Insertion loss	dB	-1	
Return channel			
Bandwidth	MHz	5-65	
Gain	dB	-4	
Maximum output level (-35dBc 2 toni)	dBμ	100	
Insertion loss	dB	-1	
Main features			
Current cons.	mA, V	220, 14 170, 18	
Dimensions	mm	260x120x30	
Operating temperature	°C	-10+55	