

## Multiswitches

### CASCADABLE MULTISWITCHES

SKU : SWI8524STPLUS



#### SWI8524STPLUS

5-input cascadable multiswitches with active SAT and terrestrial and separate adjustment. Coupled mechanics,

#### Main Specifications

- TV Gain adjustment
- 2 gain adjustments for High band and Low band
- High insulation & 45dB'
- Low insertion loss
- High output level to cover high cable length & 100m with 6,7mm coax'
- Return path included
- Low power consumption thanks to automatic check of the satellite remote feeding,
- Standard colour coding for an easy installation

Name		SWI8524STPLUS	
Code		271057	
Inputs		4 SAT, 1 TV	
Taps		24	
<b>SAT</b>			
Bandwidth	MHz	950-2150	
Positive slope gain	dB	-2\5	
Gain adjustment	dB	15	
Maximum output level (-35dBc 2 toni)	dBm	110	
Insertion loss	dB	-4	
SAT-SAT insulation	dB	>45	

Name		SWI8524STPLUS
<b>TV</b>		
Bandwidth	MHz	85-862
Positive slope gain	dB	-7/2
Gain adjustment	dB	20
Maximum output level (-35dBc 2 toni)	dBμ	105
Insertion loss	dB	-3
<b>Return channel</b>		
Bandwidth	MHz	5-65
Gain	dB	-5
Maximum output level (-35dBc 2 toni)	dBμ	100
Insertion loss	dB	-2
<b>Main features</b>		
Current cons.	mA, V	440, 14 340, 18
Dimensions	mm	355x120x60
Operating temperature	°C	-10++55