

## Multiswitches

### CASCADABLE MULTISWITCHES

SKU : SWI8532STPLUS



#### SWI8532STPLUS

5-input cascadable multiswitches with active SAT and terrestrial and separate adjustment. Coupled mechanics.

#### Main Specifications

- TV Gain adjustment
- 2 gain adjustments for High band and Low band
- High insulation (>45dB)
- Low insertion loss
- High output level to cover high cable length (100m with 6.7mm coax)
- Return path included
- Low power consumption thanks to automatic check of the satellite remote feeding.
- Standard colour coding for an easy installation

Name		SWI8532STPLUS	
Code		271058	
Inputs		4 SAT, 1 TV	
Taps		32	
<b>SAT</b>			
Bandwidth	MHz	950-2150	
Positive slope gain	dB	-2\4	
Gain adjustment	dB	15	
Maximum output level (-35dBc 2 toni)	dBm	108	
Insertion loss	dB	-5	
SAT-SAT insulation	dB	>45	

Name		SWI8532STPLUS
<b>TV</b>		
Bandwidth	MHz	85-862
Positive slope gain	dB	-10/-4
Gain adjustment	dB	20
Maximum output level (-35dBc 2 toni)	dB <sub>M</sub>	102
Insertion loss	dB	-4
<b>Return channel</b>		
Bandwidth	MHz	5-65
Gain	dB	-6
Maximum output level (-35dBc 2 toni)	dB <sub>M</sub>	100
Insertion loss	dB	-2
<b>Main features</b>		
Current cons.	mA, V	440, 14
		340, 18
Dimensions	mm	440x120x60
Operating temperature	°C	-10++55