

## Multiswitches

### CASCADABLE MULTISWITCHESES

SKU : SWI8516PLUS



#### 5-INPUT CASCADABLE PLUS Series

5-input cascadable multiswitches with active SAT and terrestrial and separate adjustment,

#### Main Specifications

- TV Gain adjustment
- 2 gain adjustments for High band and Low band
- High insulation &45dB'
- Low insertion loss
- High output level to cover high cable length &100m with 6,7mm coax'
- Return path included
- Low power consumption thanks to automatic check of the satellite remote feeding,
- Standard colour coding for an easy installation

Name		SWI8516PLUS
Code		271063
Inputs		4 SAT, 1 TV
Taps		16
<b>SAT</b>		
Bandwidth	MHz	950-2150
Positive slope gain	dB	0\4
Gain adjustment	dB	15
Maximum output level (-35dBc 2 toni)	dBμ	108
Insertion loss	dB	-2.5
SAT-SAT insulation	dB	>45

Name		SWI8516PLUS
<b>TV</b>		
Bandwidth	MHz	85-862
Positive slope gain	dB	-8/-4
Gain adjustment	dB	20
Maximum output level (-35dBc 2 toni)	dBμ	102
Insertion loss	dB	-2
<b>Return channel</b>		
Bandwidth	MHz	5-65
Gain	dB	-6
Maximum output level (-35dBc 2 toni)	dBμ	100
Insertion loss	dB	-1
<b>Main features</b>		
Current cons.	mA, V	220, 14 170, 18
Dimensions	mm	425x120x30
Operating temperature	°C	-10++55