

Multiswitches

CASCADABLE MULTISWITCHESES

SKU : SWI504SA



5-INPUT CASCADABLE Series

5-input CASCADABLE MULTISWITCHESES with passive terrestrial and active adjustable satellite,

Main Specifications

- Active satellite $\pm 20\text{dB}$ to keep the same input signal level on outputs, passive TV
- Satellite gain adj, $\pm 20\text{dB}$ to equalize the distribution between floors.
- Satellite band up to 2300MHz
- High insulation $\pm 30\text{dB}$
- Low insertion loss, allow the signal distribution up to 6 floors without any middle amplification,
- Very high SAT output level to run long cable drop with the correct signal power at the STBs (70m with 6.7mm coax.)
- Return path included
- No power supply required
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation
- Excellent quality/price ratio

Name		SWI504SA
Code		271161
Inputs		4 SAT, 1 TV
Taps		4
SAT		
Bandwidth	MHz	950-2300
Positive slope gain	dB	-4/1
Gain adjustment	dB	20
Insertion loss	dB	-1
SAT-SAT insulation	dB	>30
TV		
Bandwidth	MHz	88-790
Gain	dB	-22
Insertion loss	dB	-3

Name		SWI504SA
Power consumption		
Tap consumption	mA	160
Max current on SAT Line	mA	2000
Max current on TV line	mA	1000
Main features		
Dimensions	mm	120x120x30
Operating temperature	°C	-10++55