

## Multiswitches

# CASCADABLE MULTISWITCHES

SKU : SWI506SA



### 5-INPUT CASCADABLE Series

5-input CASCADABLE MULTISWITCHES with passive terrestrial and active adjustable satellite,

### Main Specifications

- Active satellite &dB' to keep the same input signal level on outputs, passive TV
- Satellite gain adj,  $\pm 20$ dB' to equalize the distribution between floors.
- Satellite band up to 2300MHz
- High insulation &0dB'
- Low insertion loss, allow the signal distribution up to 6 floors without any middle amplification,
- Very high SAT output level to run long cable drop with the correct signal power at the STBs (70m with 6.7mm coax.)
- Return path included
- No power supply required
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation
- Excellent quality/price ratio

Name		SWI506SA	
Code		271162	
Inputs		4 SAT, 1 TV	
Taps		6	
<b>SAT</b>			
Bandwidth	MHz	950-2300	
Positive slope gain	dB	-4/1	
Gain adjustment	dB	20	
Insertion loss	dB	-1	
SAT-SAT insulation	dB	>30	
<b>TV</b>			
Bandwidth	MHz	88-790	
Gain	dB	-22	
Insertion loss	dB	-3	

<b>Name</b>		<b>SWI506SA</b>
<b>Power consumption</b>		
Tap consumption	mA	170
Max current on SAT Line	mA	2000
Max current on TV line	mA	1000
<b>Main features</b>		
Dimensions	mm	140x120x30
Operating temperature	°C	-10++55