

## Multiswitches

### COMPACT MULTISWITCHES

SKU : SWP912TS



#### 9-INPUT COMPACT Series

9-input COMPACT MULTISWITCHESes with dip switch to select active or passive TV gain.

#### Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop &60m with 6,7mm coax,'
- Each port has a LED which shows the correct reception of the STB DiSEqC command
- Return channel included when TV gain is passive &65MHz'
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabledd, it has to be fed by DC+PLUG
- Stand alone power supply PSU1315TS &3V, 1,5A' included with standard Male Jack connector &2,1x5,5x12; internal positive, external negative' to optimize the installation space and reduce the maintenance time
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

Name		SWP912TS	
Code		287351	
Inputs		8 SAT, 1 TV	
Taps		12	
<b>SAT</b>			
Bandwidth	MHz	950-2300	
Positive slope gain	dB	-3/1	
Maximum output level (-35dBc 2 toni)	dBμ	100	
SAT-SAT insulation	dB	>30	
<b>TV</b>			
Bandwidth	MHz	5-862 passive Active: 47-862	
Active gain	dB	0	
Passive gain	dB	-20	
Maximum output level (-35dBc 2 toni)	dBμ	Active TV gain: 95	

<b>Name</b>		<b>SWP912TS</b>
<b>Return channel</b>		
Bandwidth	MHz	Passive TV: 5-65
<b>Power consumption</b>		
Tap consumption	mA	50
Current cons.	mA, V	Active TV: 160, 13 Passive TV no power supply required
Maximum LNB current	mA	Passive TV: 1500 Active TV: 1340
<b>Main features</b>		
Dimensions	mm	170x190x40
PSU dimensions	mm	90x70x45
Operating temperature	°C	-10+ 55