

SKU: SWP916TS

Multiswitches

COMPACT MULTISWITCHES



9-INPUT COMPACT Series

9-input COMPACT MULTISWITCHESes with dip switch to select active or passive TV gain.

Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop &0m with 6,7mm coax,
- Each port has a LED which shows the correct reception of the STB DiSEqC command
- Return channel included when TV gain is passive & +65MHz'
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabledd, it has to be fed by DC+PLUG
- Stand alone power supply PSU1315TS &3V, 1,5A' included with standard Male Jack connector &,1x5,5x12; internal positive, external negative' to optimize the installation space and reduce the maintenance time
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

Name		SWP916TS
Code		287352
Inputs		8 SAT, 1 TV
Taps		16
SAT		
Bandwidth	MHz	950-2300
Positive slope gain	dB	13 /1
Maximum output level (-35dBc 2 toni)	dB ∤∕	100
SAT-SAT insulation	dB	>30
TV		
Bandwidth	MHz	5-862 passive Active: 47-862
Active gain	dB	-1
Passive gain	dB	-21
Maximum output level (-35dBc 2 toni)	dB ∤ ∕	Active TV gain: 95

Data Sheet



Name		SWP916TS
Return channel		
Bandwidth	MHz	Passive TV: 5-65
Power consumption		
Tap consumption	mA	50
Current cons.	mA, V	Active TV: 160, 13 Passive TV no power supply required
Maximum LNB current	mA	Passive TV: 1500 Active TV: 1340
Main features		
Dimensions	mm	170x190x40
PSU dimensions	mm	90x70x45
Operating temperature	°C	+10÷+55