

SKU: SWP924TS

Multiswitches

COMPACT MULTISWITCHES



9-INPUT COMPACT Series

9-input COMPACT MULTISWITCHESes with dip switch to select active or passive TV gain.

Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop (60m with 6.7mm coax.)
- Each port has a LED which shows the correct reception of the STB DiSEqC command
- Return channel included when TV gain is passive (5-65MHz)
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabledd, it has to be fed by DC-PLUG
- Stand alone power supply PSU1315TS (13V, 1,5A) included with standard Male Jack connector (2,1x5,5x12; internal positive, external negative) to optimize the installation space and reduce the maintenance time
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

Name		SWP924TS
Code		287353
Inputs		8 SAT, 1 TV
Taps		24
SAT		
Bandwidth	MHz	950-2300
Positive slope gain	dB	-5/-1
Maximum output level (-35dBc 2 toni)	dB ∤∕	100
SAT-SAT insulation	dB	>30
TV		
Bandwidth	MHz	5-862 passive Active: 47-862
Active gain	dB	-2
Passive gain	dB	-22
Maximum output level (-35dBc 2 toni)	dB ∖ ∕	Active TV gain: 95

Data Sheet



Name		SWP924TS
Return channel		
Bandwidth	MHz	Passive TV: 5-65
Power consumption		
Tap consumption	mA	50
Current cons.	mA, V	Active TV: 160, 13 Passive TV no power supply required
Maximum LNB current	mA	Passive TV: 1500 Active TV: 1340
Main features		
Dimensions	mm	230x190x40
PSU dimensions	mm	90x70x45
Operating temperature	°C	-10÷+55