

Multiswitches

COMPACT MULTISWITCHES

SKU : SWP1708TS



17-INPUT COMPACT Series

17-input COMPACT MULTISWITCHESes with dip switch to select active or passive TV gain,

Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop 860m with 6,7mm coax,'
- Each port has a LED which shows the correct reception of the STB DiSEqC command
- Return channel included when TV gain is passive 8-65MHz'
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabled, it has to be fed by DC-PLUG
- Stand alone power supply PSU1340TS (13V, 4A) included with male jack connector (2,1x5,5x12; inner positive, outer negative) to optimize the installation dimensions.
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

Name		SWP1708TS
Code		287355
Inputs		16 SAT, 1 TV
Taps		8
SAT		
Bandwidth	MHz	950-2300
Positive slope gain	dB	-4/0
Maximum output level (-35dBc 2 toni)	dBV	100
SAT-SAT insulation	dB	>30
TV		
Bandwidth	MHz	5-862 passive Active: 47-862
Active gain	dB	0
Passive gain	dB	-20
Maximum output level (-35dBc 2 toni)	dBV	TV active gain: 95

Name	SWP1708TS	
Return channel		
Bandwidth	MHz	Passive TV: 5-65
Power consumption		
Tap consumption	mA	50
Current cons.	mA, V	Active TV: 160, 13 Passive TV no power supply required
Maximum LNB current	mA	Passive TV: 4000 Active TV: 3840
Main features		
Dimensions	mm	120x310x40
PSU dimensions	mm	110x52x34
Operating temperature	°C	-10++55