

SKU: SWP1716TS

Multiswitches

COMPACT MULTISWITCHES



17-INPUT COMPACT Series

17-input COMPACT MULTISWITCHESes with dip switch to select active or passive TV gain.

Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop (60m with 6.7mm coax.)
- Each port has a LED which shows the correct reception of the STB DiSEqC command
- Return channel included when TV gain is passive (5-65MHz)
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabled, it has to be fed by DC-PLUG
- Stand alone power supply PSU1340TS (13V, 4A) included with male jack connector (2,1x5,5x12; inner positive, outer negative) to optimize the installation dimensions.
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

| Name | | SWP1716TS |
|--------------------------------------|---------------|---------------------------------|
| Code | | 287357 |
| Inputs | | 16 SAT, 1 TV |
| Taps | | 16 |
| SAT | | |
| Bandwidth | MHz | 950-2300 |
| Positive slope gain | dB | -5/-1 |
| Maximum output level (-35dBc 2 toni) | dB ∤ ∕ | 100 |
| SAT-SAT insulation | dB | >30 |
| TV | | |
| Bandwidth | MHz | 5-862 passive Active: 47-862 |
| Active gain | dB | -2 |
| Passive gain | dB | -22 |
| Maximum output level (-35dBc 2 toni) | dB \ / | TV active gain: 95 |

Data Sheet



| Name | | SWP1716TS |
|-----------------------|-------|--|
| Return channel | | |
| Bandwidth | MHz | Passive TV: 5-65 |
| Power consumption | | |
| Tap consumption | mA | 50 |
| Current cons. | mA, V | Active TV: 160, 13 Passive TV no power supply required |
| Maximum LNB current | mA | Passive TV: 4000 Active TV: 3840 |
| Main features | | |
| Dimensions | mm | 190x310x40 |
| PSU dimensions | mm | 110x52x34 |
| Operating temperature | °C | -10÷+55 |