

Multiswitches

CASCADABLE MULTISWITCHES

SKU : SWI1712TS



17-INPUT CASCADABLE Series

17-input CASCADABLE MULTISWITCHESes with dip switch to select active or passive TV gain.

Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop (60m with 6.7mm coax.)
- Each port has a LED which shows the correct reception of the STB DiSEqC command
- Return channel included when TV gain is passive (5-65MHz)
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabled, it has to be fed by DC-PLUG
- External power Supply PSU1340TS (13V, 4A) Jack Male connector (2,1x5,5x12; inner positive, outer negative) NOT included; to optimize installation dimensions.
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

Name		SWI1712TS
Code		287369
Inputs		16 SAT, 1 TV
Taps		16
SAT		
Bandwidth	MHz	950-2300
Positive slope gain	dB	-5/-1
Maximum output level (-35dBc 2 toni)	dBμV	100
Insertion loss	dB	-1\4
SAT-SAT insulation	dB	>30

Name		SWI1712TS
TV		
Bandwidth	MHz	5-862 passive Active: 47-862
Active gain	dB	-3
Passive gain	dB	-23
Maximum output level (-35dBc 2 toni)	dB μ V	Active:95
Insertion loss	dB	-4\5
Return channel		
Bandwidth	MHz	Passive TV: 5-65
Power consumption		
Tap consumption	mA	50
Current cons.	mA, V	Active TV: 160, 13 Passive TV no power supply required
Maximum LNB current	mA	Passive TV: 4000 Active TV: 3840
Main features		
Dimensions	mm	190x310x40
Operating temperature	°C	-10++55