

## Multiswitches

### COMPACT MULTISWITCHESES

SKU : SWP516TS



#### 5-INPUT COMPACT SERIES

5-input COMPACT MULTISWITCHESES with dip switch to select active or passive TV gain.

#### Main Specifications

- Satellite band up to 2300MHz
- High SAT output level to run long cable drop (60m with 6.7mm coax .)
- Each port has a LED which shows the correct reception of the STB DiSeqC command
- Return channel included when TV gain is passive (5-65MHz)
- When TV gain is passive, the product is entirely fed by tap ports; only when TV active is enabled, it has to be fed by DC-PLUG
- Stand alone power supply PSU1315TS (13V, 1,5A) included with standard Male Jack connector (2,1x5,5x12; internal positive, external negative) to optimize the installation space and reduce the maintenance time
- Space reduced thanks to the matrix system with both sided connectors
- Standard colour coding for an easy installation

Name		SWP516TS
<b>Code</b>		287520
Inputs		4 SAT, 1 TV
Taps		16
<b>SAT</b>		
Bandwidth	MHz	950-2300
Positive slope gain	dB	-3/1
Maximum output level (-35dBc 2 toni)	dBV	100
SAT-SAT insulation	dB	>30
<b>TV</b>		
Bandwidth	MHz	5-862 passive Active: 47-862
Active gain	dB	-1
Passive gain	dB	-21
Maximum output level (-35dBc 2 toni)	dBV	Active TV gain: 92

Name		SWP516TS
<b>Return channel</b>		
Bandwidth	MHz	Passive TV: 5-65
<b>Power consumption</b>		
Tap consumption	mA	40
Current cons.	mA, V	Active TV: 160, 13 Passive TV no power supply required
Maximum LNB current	mA	Passive TV: 1500 Active TV: 1340
<b>Main features</b>		
Dimensions	mm	110x130x40
PSU dimensions	mm	90x70x45
Operating temperature	°C	-10++ 55