

FTTx Terminal Box wall mounted with 2SC/APC adapter /pigtail/sleeve for splice terminated drop fiber cables

FTTxBox-02



Product Summary

FTTx Terminal Box wall mounted for splice terminated drop fiber cables. Suitable for use in system installations FTTx FTTh FTTb FTTr has a complete set of sub-devices included 2SC/APC pigtail, 2SC/APC adapter, 2protection sleeve and Expansion bolts for the outlet wall-mounted

Features & Benefits:

1. Support termination, splicing and storage for fiber optic cable systems.
2. Compact structure and perfect fiber management.
3. Engineered fiber routing protect bend radius through the unit to ensure signal integrity.
4. Applicable for desk-mount or wall-mounted and compatible with flush-mount outlet.
5. Working Temperature: $-25^{\circ}\text{C} \sim +60^{\circ}\text{C}$; Atmospheric
6. Pressure: $70\text{kPa} \sim 106\text{kPa}$;
7. Relative Humidity: $\leq 85\%$ ($+30^{\circ}\text{C}$) ;
8. Connector Repeatability: >1000 ;
9. Connector Specification: IL: $\leq 0.2\text{dB}$; RL: $\geq 50\text{dB}$

Specifications:

Parameter	Value	Remark
Model	FTTxBox-02	
Outside Dimension (mm)	86x86x25	
Material	ABS	
Color	White	
Storage of fibers	G.657	
Splice capacity	2fiber	
Splice Method	Fusion Splice	40mm Sleeve
Adapter type and count	2 SC/APC	
Input cable	3mm or figure 8 (2x3mm)	From side or bottom

