



LANKO

231 WEATHERPROOF



Floor & Surface
Protection

WATER REPELLENT AGENT



CHARACTERISTICS

- Protection against water.
- Does not alter surface appearance.
- Excellent penetration.
- Weather resistant.

DESCRIPTION

A ready-to-use and solvent-based agent to protect horizontal and vertical surfaces against water and pollution.

USES

- Interior / Exterior.
- Substrates : concrete, mortar, light weight block, roof-tile, brick, stone.

WORK INSTRUCTIONS

Surface Preparation

1. Surface must be clean, dry, and free of dust, oil, paint.
2. For fresh concrete, allow a minimum of 28 days curing.

Product Preparation

1. LANKO 231 WEATHERPROOF is a ready to use product.
Stir the product before using.

Product Application

1. Apply 1st coat by brush, roller or spray.
2. Allow a sufficient drying time so that it is not drawn off while applying the 2nd coat.
3. Best results are obtained by applying the product until the substrate become saturated.
4. Allow 24 hours before traffic.



Weather Resistant



Improve
Waterproofing
Property



Stain Free

COVERAGE

- Concrete : 0.25 – 0.5 Litres/sq.m.
- Mortar : 0.5 – 0.8 Litres/sq.m.
- Cellular concrete : 0.5 – 1 Litres/sq.m.

PACKAGING

- 5 Litres container.

STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.

ISO 9001
ISO 14001
OHSAS 18001
BUREAU VERITAS
Certification



PRECAUTIONS


- Temperature range for use : 5°C to 35°C.
- Do not apply in full sunlight or on hot substrate.
- Wear gloves and safety goggles.

SPECIFICATIONS

Appearance : Milky white liquid

Density : 1

Time to recovery	Evaluation
Concrete	Excellent
Cellular concrete	Excellent
Roofing tiles and bricks	Excellent
Natural stonework	Variable
Hydraulic mortar coating	Excellent
Fibrous cement	Very good



e-learning VDO

ParexGroup Company Limited. 183 Regent House Building, Rajdamri Road., Lumpini, Bangkok 10330

*The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.