



# LANKO

# 235 PROTECT



Floor & Surface Protection

## WATER AND OIL REPELLENT AGENT



### CHARACTERISTICS

- Protection against water, oil and grease.
- Weather resistant.
- Prevent dust and stain.
- Prevent fungus growth.

### DESCRIPTION

A ready-to-use and solvent-based agent to protect horizontal and vertical surfaces against water and pollution.

### USES

- Interior / Exterior.
- Substrates : concrete, mortar, light weight block, roof-tile, brick, stone.

### WORK INSTRUCTIONS

#### Surface Preparation

1. Surface must be clean, dry, and free of dust, oil, paint.
2. For fresh concrete, allow a minimum of 28 days curing.

#### Product Preparation

1. LANKO 235 PROTECT is a ready to use product. Stir the product before using.

#### Application

1. Apply 1<sup>st</sup> coat by brush soaking or spraying.
2. Best results are obtained by applying the product until the substrate become saturated. If required, 2<sup>nd</sup> coat can be applied in 2-3 minutes after the 1<sup>st</sup> coat.
3. Allow 24 hours before traffic.



Stain Free



Prevent Black Mold



Anti Dust

### COVERAGE

- 0.04-0.7 Litres./sq.m.

### PACKAGING

- 5 Litres container.

### STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.

ISO 9001  
ISO 14001  
OHSAS 18001  
BUREAU VERITAS  
Certification



## PRECAUTIONS

- Temperature range for use : 5°C to 35°C.
- Do not apply in full sunlight or on hot substrate.
- Wear gloves and safety goggles.

## SPECIFICATIONS

<b>Appearance</b>	<b>: Amber liquid</b>
<b>Density</b>	<b>: 1</b>
<b>pH</b>	<b>: 5-8</b>
<b>Solid content</b>	<b>: 17-25</b>

Time to recovery	Evaluation
Concrete	Excellent
Cellular concrete	Excellent
Roofing tiles and bricks	Excellent
Natural stonework	Variable
Hydraulic mortar coating	Excellent
Fibrous cement	Very good



e-learning VDO

**ParexGroup Company Limited.** 183 Regent House Building, Rajdamri Road., Lumpini, Bangkok 10330

\*The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.