



LANKO

244 TUFSEAL



Floor & Surface
Protection

WATER, OIL CHEMICAL REPELLENT AGENT



CHARACTERISTICS

- Protection against water, oil grease and chemical agents.
- Weather resistant.
- Prevent dust and stain.
- Prevent fungus growth.

DESCRIPTION

A ready-to-use and acrylic agent to protect horizontal and vertical surfaces against water, oil, grease, pollution and chemical.

USES

- Interior / Exterior.
- Substrate : concrete, mortar, light weight block, roof-tile, brick, stone.

WORK INSTRUCTIONS

Surface Preparation

1. Surface must be clean, dry, and free of dust, oil, paint.
2. For fresh concrete, allow a minimum of 28 days curing.

Product Preparation

1. LANKO 244 TUFSEAL is a ready to use product.
Stir the product before applying.

Application

1. Apply 1st coat by brush roller or spray.
2. Allow a sufficient drying time for 30 minutes so that it is not drawn off while applying the 2nd coat.
3. Allow 2 hours before traffic.



Weather Resistant



Improve
Waterproofing
Property



Stain Free

COVERAGE

- 0.1-0.15 Litres/sq.m.

PACKAGING

- 1 Litre container.

STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.



PRECAUTIONS



- Temperature range for use : 5°C to 35°C.
- Do not apply in full sunlight or on hot substrate.
- Wear gloves and safety goggles.

SPECIFICATIONS

Appearance : Amber liquid

Density : 1

Open to light traffic (Hours) : 17-25



e-learning VDO

ParexGroup Company Limited. 183 Regent House Building, Rajdamri Road., Lumpini, Bangkok 10330

*The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.