



# LANKO

# 322 PROOF



Admixture

## WATERPROOFING AND PLASTICISER FOR CONCRETE AND MORTAR



### CHARACTERISTICS

- Improve waterproofing.
- Reduce cracking.
- No color effect.

### DESCRIPTION

A liquid plasticiser for improvement of waterproofing, reduce cracking and air bubbles.

### USES

- Wet area.
- Water basin and tank.
- Swimming pool.
- Concrete and mortar.

### WORK INSTRUCTIONS

#### Product preparation

1. Mix 2.50 cc. of Lanko 322 PROOF with clean water per one 50 kg. bag of portland cement or 0.5 % of the weight of portland cement.

#### Application

1. Apply mortar according to manufacturer standard.

### PRECAUTIONS

- Temperature range for use : 5°C to 35°C.
- Do not add to mixed mortar.
- Do not use mixing with water.
- Do not use LANKO 322 PROOF over dosage.



Improve waterproofing property



Reduce Cracking

### PACKAGING

- 5 Litres container.
- 20 Litres container.
- 200 Litres drum.

### STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.

ISO 9001  
ISO 14001  
OHSAS 18001  
BUREAU VERITAS  
Certification

