



LANKO

461 ACRYLIC PRIMER



Waterproofing

PRIMER FOR WATERPROOFING MEMBRANE AND WALL COATING SYSTEM.



CHARACTERISTICS

- **Bonding agent.**
- **Reduce dust.**
- **Increase abrasion resistance.**

DESCRIPTION

A primer, sealer and bonding agent to prepare floor surfaces prior to the application of waterproofing membrane & wall coating system.

USES

- Roof and wall primer.
- Substrates : concrete, render, metal, cement sheet, masonry, brick.

WORK INSTRUCTIONS

Surface Preparation

1. Surface must be clean and without any trace of oil.

Application

1. Apply LANKO ACRYLIC PRIMER to clean floor with roller, brush and squeegee.
2. Allow to dry till clear film appears.
3. Primer is dry when milkiness disappears.

PRECAUTIONS

- Temperature range for use : 5°C to 35°C.
- Water tank must be rinsed prior to filling.
- Do not apply in full sunlight.
- Protect for 24 hours in case of heavy rain or direct sun.

SPECIFICATIONS

Appearance	: Grey powder and white liquid
Particle size (mm.)	: 0.04-0.3
Paste density (kg./L.)	: 1.5-1.6



Abrasion Resistant



Reduce Air Bubble Effect

PACKAGING

- 20 litres containers.
- 5 litres containers.

STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.

