



# LANKO

# 612 ACRYLIC



Sealants

## ACRYLIC SEALANT



Can Paint Over

### CHARACTERISTICS

- For joint size: 4 to 12 mm.
- No primer required.
- 2 Colors available: Grey , White.

### DESCRIPTION

A single component acrylic sealant.

### USES

- Interior.
- Sealing crack before painting.
- Recommended for porous substrates.
- Substrates: wood, metal, door frame, concrete, natural stone and tile.

### WORK INSTRUCTIONS

#### Surface Preparation

1. Surface must be clean, dry, free of dust, oil grease and any contaminations that could harm bonding.
2. Backing rod can be used to reduce joint depth.

#### Primer Preparation

1. Use primer if the substrate is very porous.

#### Application

1. Use sealant gun and squeeze into the joint.
2. Compact the sealant into the joint by using putty knife.  
Smooth the joint with figure and soapy water.
3. Remove the adhesive tape before the sealant cures.

### COVERAGE

- 300 ml. cartridge / 3 m.  
(1x1 cm. joint).

### PACKAGING

- 300 ml. cartridge.

### STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.

ISO 9001  
ISO 14001  
OHSAS 18001  
BUREAU VERITAS  
Certification



## PRECAUTIONS

- Temperature range for use : 5°C to 35°C.
- Keep out of reach of children.

## SPECIFICATIONS

Appearance before curing	: Paste
Appearance after curing	: Rubber
Paste density	: 1.5
Tack free (min.)	: 30 min.



094 551 5458



02 651 8003



[parexgroup.co.th](http://parexgroup.co.th)



e-learning VDO

**ParexGroup Company Limited.** 183 Regent House Building, Rajdamri Road., Lumpini, Bangkok 10330

\*The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.

