



GRP5.12-WLV

Low Voltage Battery



Powered by Solar

KEY FEATURES

- Easy installation, plug and play design
- Flexible capacity, Max.15pcs in parallel to extend capacity
- Safe & reliable, Lithium Iron Phosphate (LFP) Cell
- LED Display, SOC, Battery state

GRP5.12-WLV

Battery Parameter

Battery Cell	LiFePO ₄
Battery Energy	5120Wh
Nominal Capacity	100Ah
Depth of Discharge	80%
Nominal Voltage	51.2V
Voltage Range	43.2Vdc ~ 56.16Vdc
Nominal Charge / Discharge Current	50A
Max. Charge/Discharge Current	100A
Dimension (W x H x D)	520 x 470 x 141.5 mm
Weight	47.2kg
Installation	Wall-mounted / Floor-standing
Temperature of Charge	0 ~ 55°C
Temperature of Discharge	-20°C ~ +60°C
Protection Degree	IP65
Parallel Units	Up to 15
Communication Port	RS485, CAN
Display	LED
Operation Humidity	5% ~ 95%
Max. Operating Altitude	2000m
Cycle Life	6000@80% DOD, 25°C , 0.5C
Certification	CE, IEC, UN38.3, MSDS

บริษัท ซีบีซี อินเตอร์เนชั่นแนล จำกัด
56/12-15 ซอยพระยาสุเรนทร์ 45
แขวงสามวาต:ตะวันออก เขตคลองสามวา
กรุงเทพฯ 10510
โทรศัพท์ : +66 2902 6106-8
โทรสาร : +66 2914 3009

CBC International Limited.
56 /12-15 Soi Prayasuren 45
Samwathawantok, Klongsamwa
Bangkok 10510
Tel : + 66 2902 6106-8
Fax : + 66 2914 3009

cbcinter.co.th
cbcinter.com
E-mail : info@cbcinter.com