






# YI Series // // // // // // // // // // //



## **Embedded AC Drives**

## 230 V devices, technical data;

	α				A			
	0.25	0.37	0.55	0.75	0.37	0.55	0.75	1.1
<b>Electrical data</b>								
Recommended motor rating <sup>1)</sup> [kW]	0.25	0.37	0.55	0.75	0.37	0.55	0.75	1.1
Grid voltage	1 x 100 VAC -15 %...230 VAC +10 % 140 VDC -15 %...320 VDC +10 %							
Grid frequency	50/60 Hz ± 6%							
Mains configurations	TN / TT / IT (option)				TN / TT			
Line current [A]	4.5	4.5	5.8	7.3	4.5	5.6	6.9	9.2
Rated current output eff. [IN at 8 kHz]	1.4	2.2	2.7	3.3	2.3	3.2	3.9	5.2
Min. brake resistance [ Ω]	-				50			
Overload for 60 sec.	150 %							
Switching frequency	4 kHz, 8 kHz, 16 kHz, (factory setting 8 kHz)							
Output frequency	0 Hz – 400 Hz							
Mains cycles of operation / restart	Every 2 min.							
DIN EN 61800-5 touch current	< 10 mA <sup>2)</sup>							
<b>Functions</b>								
Protective function	Overvoltage and undervoltage, I <sup>2</sup> t restriction, short-circuit, ground leak, motor and drive controller temperature, stall prevention, blocking detection, PID dry run protection							
Software functions	Process control (PID controller), fixed frequencies, data record changeover, flying restart, motor current limit							
Soft PLC	IEC61131-3, FBD, ST, AWL							
<b>Mechanical data</b>								
Housing	Plastic adapter plate / aluminium die-cast casing				Two-part aluminium die-cast casing			
Dimensions [L x W x H] mm	187 x 126 x 70		187 x 126 x 80		233 x 153 x 120			
Weight including adapter plate	1.5 kg				3.9 kg			
Protection class [IPxy]	IP 65							
Cooling	Passive cooling							
<b>Environmental conditions</b>								
Ambient temperature	-10 °C (non-condensing) to +40 °C (50 °C with derating)							
Storage temperature	-25 °C...+85 °C							
Altitude of the installation location	Up to 1000 m above sea level / over 1000 m with reduced performance (1% per 100 m) / above 2000 m see operating manual							
Relative air humidity	≤ 96 %, condensation not permitted.							
Vibration resistance (DIN EN 60068-2-6)	50 m/s <sup>2</sup> ; 5...200 Hz <sup>3)</sup>							
Shock resistance (DIN EN 60068-2-27)	300 m/s <sup>2</sup>							
EMC (DIN-EN-61800-3)	C2				C1			
Certificates and conformity	  							

	α		A	
	Standard	Basic	Standard	Standard
<b>Interfaces</b>				
Application circuit board model	Standard	Basic	Standard	Standard
I/O interfaces	2 DI / 1 DO / 1 AI / - AO / 1 relay	2 DI / 1 DO / 1 AI / - AO / - relay	4 DI / 2 DO / 2 AI / 1 AO / 2 relays	
Potentiometer on device	Accessories	Option	Option	
Foil keypad	Option	Option	Option	
MMI option	-	Option	Option	
Internal power supply	24 VDC, 100 mA / 10 VDC, 30 mA / short-circuit proof			
External feed-in 24 VDC	-	-	24 VDC +/-15 %	
Fieldbus integrated	Modbus RTU			
Fieldbus option	CANopen	-	CANopen/ PROFIBUS / PROFINET / EtherCAT / Sercos III	


Technical data for 230 V devices (subject to technical changes)

<sup>1)</sup> Recommended motor rating (4-pole asynchr. motor) is given based on the 230 VAC supply voltage.

<sup>2)</sup> With 1LA7 asynchronous motor, motor-mounted

<sup>3)</sup> Combined vibration test, part 4, severity 2 in accordance with FN942017

## 400 V devices, technical data;

Sizes	A				B			C		D			
Recommended motor rating <sup>1)</sup> [kW]	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11.0	15.0	18.5	22.0
Grid voltage	3 x 200 VAC -10 %...480 VAC +10 % 280 VDC -10 %...680 VDC +10 %												
Grid frequency	50/60 Hz ± 6 %												
Mains configurations	TN / TT												
Line current [A]	1.4	1.9	2.6	3.3	4.6	6.2	7.9	10.8	14.8	23.2	28.2	33.2	39.8
Rated current output eff. [IN at 8 kHz]	1.7	2.3	3.1	4.0	5.6	7.5	9.5	13.0	17.8	28.0	34.0	40.0	48.0
Min. brake resistance [ Ω]	100				50			50		30			
Overload for 60 sec. in %	150												130
Switching frequency	4 kHz, 8 kHz, 16 kHz, (factory setting 8 kHz)												
Output frequency	0 Hz - 400 Hz												
Mains cycles of operation / restart	Unlimited										2 min.		
DIN EN 61800-5 touch current	< 3.5 mA <sup>2)</sup>												
Protective function	Overvoltage and undervoltage, I <sup>2</sup> t restriction, short circuit, ground leak, motor and drive controller temperature, stall prevention, blocking detection, PID dry run protection												
Software functions	Process control (PID controller), fixed frequencies, data record changeover, flying restart, motor current limit												
Soft PLC	IEC61131-3, FBD, ST, AWL												
Housing	Two-part aluminium die-cast casing												
Dimensions [L x W x H] mm	233 x 153 x 120				270 x 189 x 140			307 x 223 x 181		414 x 294 x 232			
Weight including adapter plate	3.9 kg				5.0 kg			8.7 kg		21.0 kg			
Protection class	IP 65										IP 55		
Cooling	Passive cooling										Active cooling		
Ambient temperature	-25 °C (non-condensing) to +50 °C (without derating)												
Storage temperature	-25 °C...+85 °C												
Altitude of the installation location	Up to 1000 m above sea level / over 1000 m with reduced performance (1 % per 100 m) / above 2000 m see operating manual												
Relative air humidity	≤ 96 %, condensation not permitted.												
Vibration resistance (DIN EN 60068-2-6)	50 m/s <sup>2</sup> ; 5...200 Hz <sup>3)</sup>												
Shock resistance (DIN EN 60068-2-27)	300 m/s <sup>2</sup>												
EMC (DIN-EN-61800-3)	C2												
Certificates and conformity	  												

Size	A, B, C	A, B, C, D	
Application circuit board model	Basic	Standard	Functional safety
I/O interfaces	2 DI / 1 DO / 1 AI / - AO / - relay	4 DI / 2 DO / 2 AI / 1 AO / 2 relays	4 DI / 2 DO / 2 AI / 1 AO / - relay / 2 STO channels
Potentiometer on device	Option	Option	Option
Foil keypad	Option	Option	Option
MMI option	Option	Option	Option
Internal power supply	24 VDC, 100 mA / 10 VDC, 30 mA / short-circuit proof		
External feed-in 24 VDC	-	24 VDC +/-15 %	24 VDC +/-15 %
Fieldbus integrated	Modbus RTU		
Fieldbus option	-	CANopen / PROFIBUS / P ROFINET / EtherCAT / Sercos III	

Technical data for 400 V devices (subject to technical changes)

<sup>1)</sup> Recommended motor rating (4-pole asynchr. motor) is given based on the 400 VAC supply voltage.

<sup>2)</sup> With 1LA7 asynchronous motor, motor-mounted

<sup>3)</sup> Combined vibration test, part 4, severity 2 in accordance with FN942017

# YI Series - "Smart connections" on five levels

## 1 The YI Drive

- IP65 protection class
- Integrated soft PLC
- Pre-fitted cable glands
- Fan-free design up to 7.5 kW
- Robust and vibration-resistant housing concept
- STO functional safety

## 3 Operation and observation

- Potentiometer
- M12 RS485 service interface
- Integrated foil keypad
- MMI handheld controller
- MMI cover option
- Touch operating terminal
- INVEOR PC software

## 2 Communication

- CANopen
- PROFINET
- EtherCAT
- PROFINET
- MODBUS RTU
- SERCOS  
the automation bus

## 4 Motor adaptations

- Robust and vibration-resistant adapter concept
- Motor adapter concept compatible with all commercially available motors

## 5 Control process

- IE1, IE2, IE3, IE4: for synchronous and asynchronous motors



**Yilmaz (Thailand) Co., Ltd.**  
 1/19 Moo 1 Pimpa, Bangpakong  
 Chachoengsao 24130, (Thailand)  
 Mobile : 06-3515-2899 TAX ID. 0245562000961  
 E-mail : yilmazthailand@gmail.com www.yilmazthailand.com

