



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Monday, February 08, 2016** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=38570&Standard=061&>

NSF/ANSI 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).

RectorSeal

<http://www.rectorseal.com>

2601 Spenwick Drive

Houston, TX 77055

United States

713-263-8001

[Visit this company's website \(http://www.rectorseal.com\)](http://www.rectorseal.com)

Facility : # 1 USA

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Fluxes			
NOKORODE® 95/5 Pre-Tinning Paste Flux[G]	>= 1/2"	C. HOT	FLX
NOKORODE® Aqua-Flux™[G]	>= 1/2"	C. HOT	FLX
NOKORODE® Regular Paste Flux[G]	>= 1/2"	C. HOT	FLX

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for “lead free” plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Solvent Cements

Sam™ CL-3[2] [G]	>= 1/2"	C. HOT	CLE
Sam™ CL-3L - Low VOC[2] [G]	>= 1/2"	C. HOT	CLE

[2] This product is a cleaner that is intended to be used directly before application of a solvent cement. An additional primer is not required.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Thread Compounds

Blue+™[G]	>= 1/2"	C. HOT	TC
No. 100 Virgin™[1] [G]	>= 1/2"	C. HOT	TC
Pure White Teflon Pipe Compound[1] [3] [G]	>= 1/2"	C. HOT	TC
RectorSeal® No. 5®[1] [G]	>= 1/2"	CLD 23	TC
RectorSeal® T Plus 2®[1] [G]	>= 1/2"	C. HOT	TC
Tru-Blu™[1] [G]	>= 1/2"	CLD 23	TC

[1] Products were prepared for evaluation according to manufacturer's instructions.

[3] DuPont Registered Trademark.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility : # 3 USA

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Lubricants [G]			
RectorSeal® Pipe Lube	>= 1/2"	CLD 23	LUB

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for

“lead free” plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Number of matching Manufacturers is 1

Number of matching Products is 12

Processing time was 1 seconds