



RectorSeal® T Plus 2®



“เร็คโตซีล” ทีพลัสทู เป็นน้ำยาทาเกลียวกันรั่วซึมผสม เทปลอน มีลักษณะข้น เหนียว ไม่แข็งตัว ทนต่อแรงดันลม น้ำ น้ำมันหล่อลื่น น้ำมันไฮดรอลิก แก๊สแอลพีจี แก๊สธรรมชาติ น้ำมันพีช แอมโมเนีย ฟรีออน กรดเจ็จจาง ฯลฯ

สามารถใช้งานได้กับวัสดุต่างๆ หลากหลายชนิด เช่น เหล็กดำ, กัลวาไนซ์, สแตนเลส, ทองเหลือง, ทองแดง, อลูมิเนียม, PE, PVC, CPVC, ไฟเบอร์กลาส, เอบีเอส ฯลฯ

*** ไม่ต้องใช้ค้ายหรือเชือกปอพันเกลียว ***

- ทนแรงดันใช้งานได้ถึง 10,000 PSI (ของเหลว) และ 2,000 PSI (แก๊ส)
- ช่วงอุณหภูมิใช้งาน (-26° C ถึง 177° C)
- น้ำยาไม่แห้งแข็งตัวติดกระป๋อง
- หลังการติดตั้งสามารถถอดออกได้ง่าย
- สามารถประหยัดน้ำยาทาเกลียวได้อย่างน้อย 30% เมื่อเปรียบเทียบกับน้ำยาทาเกลียวทั่วไปที่มีขายในท้องตลาด
- สามารถใช้งานรับแรงดันได้ทันที เมื่อติดตั้งเสร็จ
- ใช้ทาเกลียวตัวผู้ – ตัวเมียที่ได้มาตรฐานเดียวกันเท่านั้น

*** ผลิตและนำเข้าจากประเทศสหรัฐอเมริกา***



DURMAST CO., LTD.

48 Moo 2, Soi Watsripawat, Paduangawat Rd., Salangrang, Bangkuay, Nonthaburi, Thailand 11130

Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastsales@gmail.com

RectorSeal® T Plus 2®

Pipe Thread Sealant with PTFE

DESCRIPTION

RectorSeal® T Plus 2 ® is a non-hardening thread sealant containing PTFE plus synthetic fibers. These fibers dispersed in a resinous base combined with inert mineral fillers provide maximum sealing performance. Its low coefficient of friction allows tighter joint makeup with lower torque. It also breaks out easily without galling, seizing, or damaging threads. It is excellent for service where immediate pressurization is necessary. RectorSeal® T Plus 2® is non-toxic in accordance with NSF Standard 61. In addition, it is approved and listed with the Canadian Standards Association (CSA).

CHARACTERISTICS

- PTFE enriched
- Non-staining and non-separating
- Allows immediate pressurization
- Lubricates and protects threads
- For use with potable water (hot or cold)
- Low odor
- Non-setting and will not dry out in the can
- Lead free and contains no other metals
- Formulated for plastic and metal pipe
- For pressures up to 10,000 psi (liquids) and 2,000 psi (gases)
- Smooth easy application
- Multipurpose
- Non-flammable

APPLICATIONS

RectorSeal® T Plus 2® can be used on a variety of metal and plastic piping including iron, galvanized steel, stainless steel, brass, copper, aluminum, polyethylene, reinforced fiberglass, PVC, ABS and CPVC including FlowGuard Gold®**.

RectorSeal® T Plus 2® is recommended for pipe carrying:

Acids, Dilute	Heating Oils	Natural Gas
Air, Compressed	Helium, Gaseous	Nitrogen, Gaseous
Ammonia- Gaseous, Liquid	Hydraulic Oils	Soap, Liquid
Aliphatic Solvents	Hydrogen, Gaseous	Vegetable Oils
Caustic, Dilute	Inert Gases, Gaseous	Water (Hot or Cold)
Cutting Oils (Low Aromatic)	Kerosene	
Refrigerants	Liquified Petroleum Gases (Butane, Propane, Mixtures)	
Mineral Oils	Not recommended for oxygen.	



DURMAST CO., LTD.

48 Moo 2, Soi Watsripawat, Paduangasawat Rd., Salagrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastales@gmail.com

PACKAGING

Code	Size	Qty. Per Case	Lbs. per Case	Cu. Ft Per Case
23710	1 3/4 oz. display (50 g)	24 tubes	4	.13
23720	1 3/4 oz. bulk (50 g)	48 tubes	6	.23
23631	1/4 pint brush top (118 ml)	24 cans	12	.18
23551	1/2 pint brush top (237 ml)	24 cans	21	.45
23431	Pint brush top (473 ml)	12 cans	19	.43
23391	Quart brush top (946 ml)	12 cans	34	.78
23271	Gallon friction top (3.8 L)	4 cans	45	.94
23191	5 Gallon (18.9 L)	1 pail	58	1.12
23112	55 Gallon (208 L)	1 drum	638	9.01

INSTRUCTIONS

1. Stir before using.
2. Wipe threads clean.
3. For pipe diameters up to 1 1/4", apply to male threads only. For larger sizes, apply to both male and female threads.
4. Join pipe per ANSI Standards. Piping may be placed into service immediately.

PRECAUTIONS

Do not take internally. Do not burn - fumes may be harmful. Wash after handling.

FIRST AID: For any overexposure, get immediate medical attention after first aid is given.

Eyes - Flush 15 minutes with clean water.

Skin - Wash with soap and water.

Inhalation for burning fumes - Remove to fresh air.

Ingestion - Only if conscious, give large amounts of water and INDUCE VOMITING. Obtain medical attention.

FIRE AND SPILLS: For fire, use water fog, CO2, foam, or dry chemicals. Wipe up spills to prevent footing hazard.

STORAGE AND HANDLING: Keep container closed when not in use. Do not reuse empty container.

KEEP OUT OF REACH OF CHILDREN.



DURMAST CO., LTD.

48 Moo 2, Soi Watsripawat, Paduangawat Rd., Salagrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastales@gmail.com

SPECIFICATIONS

Wt/Gal @ 77 degree F	11.0 +- .5 lbs/gal.
Flash Point SETA CC	Greater than 300 degree F
Non-volatiles	100%
Color	White
Shelf Life	2 years minimum
Federal Specification	TT-S-1732



"Meets ANSI LC 7-2009 Working Temperature Range -40°F to 125°F.

Maximum Working Pressure: 125 psi.

For Use With Natural Gas & LP (VAPOR STATE ONLY).

Use on Steel, Galvanized Steel, Iron, Brass, Copper and Aluminum.

For Pipe Size Up To And Including 1 1/4 Inch".

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects.

THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.



DURMAST CO., LTD.

48 Moo 2, Soi Watsriprawat, Paduangawat Rd., Salagrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastsales@gmail.com