



SAFETY DATA SHEET

METACAUWK® INDUSTRIAL CABLE COATING

Industrial strength coating for power cables

SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Name
Metacaulk® Industrial Cable Coating

Product Codes
50250

Chemical Family
Organic/Inorganic

Use
Fire retardant latex coating

Manufacturer's Name
The RectorSeal Corporation
2601 Spenwick Drive
Houston, Texas 77055 USA

HMIS Codes
Health 1
Flammability 1
Reactivity 0
PPI B

Date of Validation
January 23, 2015
Date of Preparation
September 19, 2011

SECTION 2 – HAZARDS IDENTIFICATION

GHS CLASSIFICATION

Physical Hazards:

None

Health Hazards

Acute Toxicity:

Oral: Not Classified
Dermal: Not Classified
Inhalation: Not Classified
Skin Corrosion/Irritation: Not Classified
Serious Eye Damage/Eye Irritation: Not Classified
Respiratory or Skin Sensitization: Not Classified
Germ Cell Mutagenicity: Not Classified
Carcinogenicity: Not Classified
Reproductive Toxicology: Not Classified



DURMAST CO., LTD.

48 Moo 2, Soi Watsripawat, Paduangsawat Rd., Salagrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastsales@gmail.com

METACAULK® INDUSTRIAL CABLE COATING

Target Organ Systemic Toxicity - Single Exposure: Not Classified
Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

ENVIRONMENTAL HAZARDS

Hazardous to the Aquatic Environment: Not Classified
Acute aquatic toxicity: Not Classified
Chronic aquatic toxicity: Not Classified
Bioaccumulation potential: Not Classified
Rapid degradability: Not Classified

GHS Label elements, including precautionary statements

Pictogram: None

Signal Word: None

Hazard Statements:
None

Precautionary Statements:
P102 - Keep out of reach of children.
P264 - Wash hands thoroughly after handling.

Summary Of Acute Hazards

May cause skin irritation.

Route Of Exposure, Signs And Symptoms

INHALATION

Spray applications of this material may create aerosols, which may be irritating to the upper respiratory tract, nose, and throat.

EYE CONTACT

Contact may cause eye irritation.

SKIN CONTACT

Contact may cause skin irritation.

INGESTION

Possible irritation to mucous membranes of the mouth, throat, and stomach.

SUMMARY OF CHRONIC HAZARDS

None known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Persons with pre-existing skin conditions or chemical allergies may be more susceptible to contact effects of the cured elastomer.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient:	Aluminum oxide
Percentage by weight:	10-25
CAS Number:	1344-28-1
EC#:	215-691-6



DURMAST CO., LTD.

48 Moo 2, Soi Watsripawat, Paduangawatt Rd., Salagrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastsales@gmail.com

METACALK® INDUSTRIAL CABLE COATING

Ingredient:	Zinc borate
Percentage by weight:	1-5
CAS Number:	1332-07-6
EC#:	215-566-6

SECTION 4 – FIRST AID MEASURES

If inhaled:	Not a respiratory irritant.
If on skin:	Wash with soap and water. If irritation occurs, seek medical attention.
If in eyes:	Immediately flush with large amounts of water. If irritation occurs, seek medical attention.
If swallowed:	If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

Foam, dry chemical, carbon dioxide or water fog.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

Unusual Fire And Explosion Hazards: None known.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

SECTION 7 – HANDLING AND STORAGE

Precautions To Be Taken In Handling And Storing: Keep container closed and upright when not in use. To prevent freezing and possible rupture of container, do not store below 35°F.

Other Precautions: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all product precautions. Do not reuse empty containers.

KEEP OUT OF REACH OF CHILDREN.



METACAULK® INDUSTRIAL CABLE COATING

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients Units

Aluminum oxide

ACGIH TLV 10 mg/m³ (TWA)

OSHA PEL 10 mg/m³ (TWA)

Zinc Borate

ACGIH TLV N/D

OSHA PEL N/D

Respiratory Protection (Specify Type): None required.

Ventilation – Local Exhaust: Acceptable.

Special: N/A

Mechanical (General): Preferable.

Other: N/A

Protective Gloves: Wear rubber gloves.

Eye Protection: Safety glasses (ANSI Z-87.1 or equivalent)

Other Protective Clothing Or Equipment: Coveralls recommended.

Work/Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling point: > 212°F (100°C)

pH: 8-10

Specific gravity (H₂O = 1): N/D

Vapor pressure (mmHg): N/D

Melting point: N/D

Vapor Density (Air = 1): > 1

Evaporation rate (Ethyl Acetate = 1): 1

Appearance/Odor: Liquid

Solubility in water: Soluble

Volatile Organic Compounds (VOC) Content
(theoretical percentage by weight): 6 g/L

Flash point: None

Lower explosion limit: N/D

Upper explosion limit: N/D



METACAULK® INDUSTRIAL CABLE COATING

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: None.

Incompatibility (Materials To Avoid): None known.

Hazardous Decomposition Products: CO, CO₂ and fragmented hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGY INFORMATION

Chronic Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Toxicology Data

Ingredient Name

(No data available unless listed below)

SECTION 12 – ECOLOGICAL INFORMATION

Ecological Data

Ingredient Name: **(No data available unless listed below)**

No data available for product.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated waste.

Disposal Method: Solidification and approved landfill.

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with federal, state, and local regulation regarding pollution.

SECTION 14 – TRANSPORTATION INFORMATION

DOT:	Non-regulated
Ocean (IMDG):	Non-regulated
Air (IATA):	Non-regulated
WHMIS (Canada):	Non-regulated



DURMAST CO., LTD.

48 Moo 2, Soi Watsriprawat, Paduangasawat Rd., Salagrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastsales@gmail.com

METACALK® INDUSTRIAL CABLE COATING

SECTION 15 – REGULATORY INFORMATION

Regulatory Data

Ingredient Name: **Aluminum oxide**

SARA 313 Yes

TSCA Inventory Yes

CERCLA RQ N/A

RCRA Code N/A

Ingredient Name: **Zinc borate**

SARA 313 Yes

TSCA Inventory Yes

CERCLA RQ 1,000 lbs.

SECTION 16 – OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200).

The information herein is given in good faith, but no warranty, expressed or implied is made.



DURMAST CO., LTD.

48 Moo 2, Soi Watsripawat, Paduangsawat Rd., Salangrang, Bangkuay, Nonthaburi, Thailand 11130
Tel. (662) 490-4445-6 Fax. (662) 490-4447 www.durmast.co.th E-mail : durmastsales@gmail.com