




2 WAY FLANGED

BALL VALVE WITH ACTUATOR

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 2 way flanged PN16 ball valve [Valpres artt. 730008 from DN25 to DN65 - 730003 from DN80 to DN200] cast iron, with ball and stem in stainless steel AISI 304, full bore, face to face to EN558 basic series 14 (DN200 basic series 27).



Art. 8P004500

With double acting pneumatic actuator series 82.

DN	25	32	40	50	65	80	100	125	150	200
PN	16	16	16	16	16	16	16	16	16	16
ACT.	DA52	DA52	DA63	DA75	DA85	DA85	DA100	DA115	DA125	DA160
KIT	RI3001	RI3001	RI3002	RI3009	RI3003	RI3003	RI3004	RI3005	RI3006	RI3039



Art. 8P004600

With spring return pneumatic actuator series 82.

DN	25	32	40	50	65	80	100	125	150	200
PN	16	16	16	16	16	16	16	16	16	16
ACT.	SR63	SR63	SR85	SR100	SR115	SR125	SR125	SR140	SR160	SR200
KIT	RI3007	RI3007	RI3009	RI3009	RI3010	RI3010	RI3005	RI3037	RI3039	RI3040



Art. 8E009***

With electric actuator series 85.

DN	25	32	40	50	65	80	100	125	150	200
PN	16	16	16	16	16	16	16	16	16	-
ACT.	VB030	VB030	VB060	VB060	VB110	VB110	VB190	VB190	VB350	-
KIT	RI3001	RI3001	RI3002	RI3002	RI3003	RI3003	RI3004	RI3004	RI3006	-
12 V										
24 V										
100 - 240 V										

Art. 8M009***


With electric actuator series 86.

DN	25	32	40	50	65	80	100	125	150	200
PN	16	16	16	16	16	16	16	16	16	-
ACT.	VB030M	VB030M	VB060M	VB060M	VB110M	VB110M	VB190M	VB190M	VB350M	-
KIT	RI3001	RI3001	RI3002	RI3002	RI3003	RI3003	RI3004	RI3004	RI3006	-
12 V										
24 V										
100 - 240 V										

***			VOLTAGE CODE		
12V AC/DC + 001		24V AC/DC + 002		100-240V AC + 004	

PRODUCT LEAFLET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Flanged PN16 stainless steel AISI 316 CF8M ball valve, full bore Split Body type [Valpres art. 765000] ISO 5211 pad direct, Fire Safe, Antistatic Device, EN558 basic series 27 face to face dimension.



Art. 8P050200

With double acting pneumatic actuator series 82.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	DA52	DA52	DA63	DA75	DA85	DA85	DA100
KIT	RI4579	RI4579	RI4581	RI4582	RI4584	RI4584	RI4586



Art. 8P050300

With spring return pneumatic actuator series 82.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	SR63	SR63	SR75	SR85	SR115	SR115	SR125
KIT	RI4580	RI4580	RI4582	RI4583	RI4585	RI4585	RI4587



Art. 8E185***

With electric actuator series 85.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	VB030	VB060	VB060	VB060	VB110	VB110	VB190
KIT	RI4579	RI4580	RI4581	RI4581	RI4584	RI4584	RI4586
12 V							
24 V							
100 - 240 V							

Art. 8M185***


Con attuatore elettrico serie 86.
With electric actuator series 86.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	VB030M	VB060M	VB060M	VB060M	VB110M	VB110M	VB190M
KIT	RI4579	RI4580	RI4581	RI4581	RI4584	RI4584	RI4586
12 V							
24 V							
100 - 240 V							

VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Flanged PN16 carbon steel WCB ball valve, full bore Split Body type [Valpres art. 765001] ISO 5211 pad direct, Fire Safe, Antistatic Device, EN558 basic series 27 face to face dimension.



Art. 8P050400

With double acting pneumatic actuator series 82.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	DA52	DA52	DA63	DA75	DA85	DA85	DA100
KIT	RI4579	RI4579	RI4581	RI4582	RI4584	RI4584	RI4586



Art. 8P050500

With spring return pneumatic actuator series 82.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	SR63	SR63	SR75	SR85	SR115	SR115	SR125
KIT	RI4580	RI4580	RI4582	RI4583	RI4585	RI4585	RI4587



Art. 8E186***

With electric actuator series 85.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	VB030	VB060	VB060	VB060	VB110	VB110	VB190
KIT	RI4579	RI4580	RI4581	RI4581	RI4584	RI4584	RI4586
12 V							
24 V							
100 - 240 V							

Art. 8M186***


With electric actuator series 86.

DN	25	32	40	50	65	80	100
PN	40	40	40	40	16	16	16
ACT.	VB030M	VB060M	VB060M	VB060M	VB110M	VB110M	VB190M
KIT	RI4579	RI4580	RI4581	RI4581	RI4584	RI4584	RI4586
12 V							
24 V							
100 - 240 V							

VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Flanged ANSI 150 stainless steel AISI 316 CF8M ball valve, full bore Split Body type [Valpres art. 766000] ISO 5211 pad direct, Fire Safe, Antistatic Device, ANSI B16.10 face to face dimension.



Art. 8P050600

With double acting pneumatic actuator series 82.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	DA52	DA63	DA75	DA85	DA100
KIT	RI4579	RI4581	RI4582	RI4584	RI4586



Art. 8P050700

With spring return pneumatic actuator series 82.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	SR63	SR75	SR85	SR115	SR125
KIT	RI4580	RI4582	RI4583	RI4585	RI4587



Art. 8E187***

With electric actuator series 85.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	VB030	VB060	VB060	VB110	VB190
KIT	RI4579	RI4581	RI4581	RI4584	RI4586
12 V					
24 V					
100 - 240 V					



Art. 8M187***

With electric actuator series 86.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	VB030M	VB060M	VB060M	VB110M	VB190M
KIT	RI4579	RI4581	RI4581	RI4584	RI4586
12 V					
24 V					
100 - 240 V					

*** VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFLET 2 WAY FLANGED VALVES WITH ACTUATOR



Flanged ANSI 150 carbon steel WCB ball valve, full bore Split Body type [Valpres art. 766001] ISO 5211 pad direct, Fire Safe, Antistatic Device, ANSI B16.10 face to face dimension.



Art. 8P050800

With double acting pneumatic actuator series 82.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	DA52	DA63	DA75	DA85	DA100
KIT	RI4579	RI4581	RI4582	RI4584	RI4586



Art. 8P050900

With spring return pneumatic actuator series 82.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	SR63	SR75	SR85	SR115	SR125
KIT	RI4580	RI4582	RI4583	RI4585	RI4587



Art. 8E188***

With electric actuator series 85.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	VB030	VB060	VB060	VB110	VB190
KIT	RI4579	RI4581	RI4581	RI4584	RI4586

12 V
24 V
100 - 240 V




Art. 8M188***

With electric actuator series 86.

SIZE	1"	1 1/2"	2"	3"	4"
PN	20	20	20	20	20
ACT.	VB030M	VB060M	VB060M	VB110M	VB190M
KIT	RI4579	RI4581	RI4581	RI4584	RI4586

12 V
24 V
100 - 240 V

*** VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004



2 way flanged ball valve, from ingot, polished, stainless steel AISI 316, full bore.



Art. 8P005100

With double acting pneumatic actuator series 82.

DN	10	15	20	25	32	40	50	65	80	100
PN	40	40	40	40	40	25	25	16	16	16
ACT.	DA52	DA52	DA52	DA52	DA63	DA63	DA63	DA85	DA85	DA85
KIT	-	-	-	-	-	-	-	-	-	-



Art. 8P005300

With spring return pneumatic actuator series 82.

DN	10	15	20	25	32	40	50	65	80	100
PN	40	40	40	40	40	25	25	16	16	16
ACT.	SR52	SR63	SR63	SR85	SR85	SR85	SR85	SR100	SR125	SR125
KIT	-	-	-	-	-	-	-	-	-	-

Art. 8E011***

With electric actuator series 85.

DN	10	15	20	25	32	40	50	65	80	100
PN	40	40	40	40	40	25	25	16	16	16
ACT.	VB015	VB015	VB015	VB030*	VB030*	VB060	VB060	VB110	VB110	VB110
KIT	-	-	-	-	-	-	-	-	-	-
12 V										
24 V										
100 - 240 V										

*Special version.



Art. 8M011***

With electric actuator series 86.

DN	10	15	20	25	32	40	50	65	80	100
PN	-	-	-	40	40	25	25	16	16	16
ACT.	-	-	-	VB030M*	VB030M*	VB060M	VB060M	VB110M	VB110M	VB110M
KIT	-	-	-	-	-	-	-	-	-	-
12 V										
24 V										
100 - 240 V										

*Special version.

***			CODICE TENSIONE - VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004			



A.P.S. CONTROL CO., LTD., THAILAND

7 SOI ON-NUCH 62 SUKHUMVIT 77 RD. ON-NUCH SUANLUANG BANGKOK 10250 WWW.APSCONTROL.CO.TH
Tel: 0 2721 1800 (Auto) Fax: 0 2721 1791 E-mail: sales@apscontrol.co.th Line ID: aps.sales Tax.ID: 010-55430-20618

Note: We are engineering partner as a total system solution provider, VALBIA manufactures a range of components to ensure cost effective and reliable about quarter-turn actuators. As a comprehensive solution provider, We have great quality control procedures. The calculate various system designs and can work together perfectly. Finally we are fully committed to maintaining environment quality together.

VALBIA S.R.L., ITALY

Note: Only excellence allows to compete in the international market. The challenge can be faced thanks to the passion and the energy of the researchers, who plan and manufacture avant-garde quality and technology, a team which is perfectly integrated for providing total, customer satisfaction; we are ready!
To ensure the quality and technical standards at the highest level, the manufacturer reserves the right to alter the specifications without notice. This documentation supersedes and replaces all previous editions.

THE VALBIA BALL VALVE © 2019 Valbia. All Rights Reserved.