



2 WAY SPLIT BODY

BALL VALVE WITH ACTUATOR

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



Split Body [Valpres art. 760000] full bore flanged PN16 ball valve, stainless steel AISI 316 CF8M, Fire Safe, Antistatic Device, face to face EN558 basic series 27, classified ATEX Ex II 2 G/D c T3.



Art. 8P011700

With double acting pneumatic actuator series 82.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250*	300*
PN	40	40	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	DA32	DA52	DA52	DA52	DA63	DA75	DA85	DA85	DA100	DA100	DA125	DA160	DA230	DA230
KIT	RI3518	RI3519	RI3520	RI3520	RI3521	RI3522	RI3522	RI3523	RI3552	RI3552	RI3553	RI3554	RI4577	RI4577

*TRUNION $\Delta p=16$ Bar.



Art. 8P011800

With spring return pneumatic actuator series 82.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250*	300*
PN	40	40	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	SR52	SR63	SR63	SR63	SR85	SR100	SR115	SR125	SR125	SR140	SR160	SR200	SR330	SR330
KIT	RI3519	RI3829	RI3525	RI3525	RI3526	RI3522	RI3527	RI3528	RI3528	RI3997	RI3554	RI3555	RI4578	RI4578

*TRUNION $\Delta p=16$ Bar.

Art. 8E053***

With electric actuator series 85.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
PN	40	40	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	VB015	VB015	VB030	VB060	VB060	VB060	VB110	VB110	VB190	VB270	VB350	-	-	-
KIT	RI3519	RI3519	RI3520	RI3525	RI3521	RI4039	RI3522	RI3523	RI3552	RI3528	RI3553	-	-	-
12 V														
24 V														
100 - 240 V														



Art. 8M053***

With electric actuator series 86.


DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
PN	-	-	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	-	-	VB030M	VB060M	VB060M	VB060M	VB110M	VB110M	VB190M	VB270M	VB350M	-	-	-
KIT	-	-	RI3520	RI3525	RI3521	RI4039	RI3522	RI3523	RI3552	RI3528	RI3553	-	-	-
12 V														
24 V														
100 - 240 V														

VOLTAGE CODE

12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004
---------------------------	---------------------------	-----------------------------

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body [Valpres art. 760040] full bore flanged PN40 ball valve, stainless steel AISI 316 CF8M, Fire Safe, Antistatic Device, face to face EN558 basic series 27, classified ATEX Ex II 2 G/D c T3.

Art. 8P024500

With double acting pneumatic actuator series 82.

DN	65	80	100	150	200*
PN	40	40	40	40	40
ACT.	DA100	DA100	DA115	DA160	DA180
KIT	RI3522	RI3552	RI3528	RI3554	RI3555

*TRUNION $\Delta p=25$ Bar.




Art. 8P024700

With spring return pneumatic actuator series 82.

DN	65	80	100	150	200*
PN	40	40	40	40	40
ACT.	SR125	SR125	SR160	SR230	SR230
KIT	RI3527	RI3528	RI3997	RI3753	RI3753

*TRUNION $\Delta p=25$ Bar.

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



Split Body [Valpres art. 760001] full bore flanged PN16 ball valve, carbon steel WCB, Fire Safe, Antistatic Device, face to face EN558 basic series 27, classified ATEX Ex II 2 G/D c T3.



Art. 8P011900

With double acting pneumatic actuator series 82.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250*	300*
PN	40	40	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	DA32	DA52	DA52	DA52	DA63	DA75	DA85	DA85	DA100	DA100	DA125	DA160	DA230	DA230
KIT	RI3518	RI3519	RI3520	RI3520	RI3521	RI3522	RI3522	RI3523	RI3552	RI3552	RI3553	RI3554	RI4577	RI4577

*TRUNION Δ p=16 Bar.



Art. 8P012000

With spring return pneumatic actuator series 82.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250*	300*
PN	40	40	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	SR52	SR63	SR63	SR63	SR85	SR100	SR115	SR125	SR125	SR140	SR160	SR200	SR330	SR330
KIT	RI3519	RI3829	RI3525	RI3525	RI3526	RI3522	RI3527	RI3528	RI3528	RI3997	RI3554	RI3555	RI4578	RI4578

*TRUNION Δ p=16 Bar.

Art. 8E054***

With electric actuator series 85.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
PN	40	40	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	VB015	VB015	VB030	VB060	VB060	VB060	VB110	VB110	VB190	VB270	VB350	-	-	-
KIT	RI3519	RI3519	RI3520	RI3525	RI3521	RI4039	RI3522	RI3523	RI3552	RI3528	RI3553	-	-	-
12 V														
24 V														
100 - 240 V														



Art. 8M054***


With electric actuator series 86.


DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
PN	-	-	40	40	40	40	16	16	16	16	16	16	16	16
ACT.	-	-	VB030M	VB060M	VB060M	VB060M	VB110M	VB110M	VB190M	VB270M	VB350M	-	-	-
KIT	-	-	RI3520	RI3525	RI3521	RI4039	RI3522	RI3523	RI3552	RI3528	RI3553	-	-	-
12 V														
24 V														
100 - 240 V														

VOLTAGE CODE

12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004
---------------------------	---------------------------	-----------------------------

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body [Valpres art. 760041] full bore flanged PN40 ball valve, carbon steel WCB, Fire Safe, Antistatic Device, face to face EN558 basic series 27, classified ATEX Ex II 2 G/D c T3.

Art. 8P024600

With double acting pneumatic actuator series 82.

DN	65	80	100	150	200*
PN	40	40	40	40	40
ACT.	DA100	DA100	DA115	DA160	DA180
KIT	RI3522	RI3552	RI3528	RI3554	RI3555

*TRUNION $\Delta p=25$ Bar.



Art. 8P024800


With spring return pneumatic actuator series 82.

DN	65	80	100	150	200*
PN	40	40	40	40	40
ACT.	SR125	SR125	SR160	SR230	SR230
KIT	RI3527	RI3528	RI3997	RI3753	RI3753

*TRUNION $\Delta p=25$ Bar.

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body type flanged ANSI 150 ball valve [Valpres art. 760005] stainless steel AISI 316 CF8M, full bore, Fire Safe, Antistatic Device, face to face ANSI B16.10, classified ATEX Ex II 2 G/D c T3.



Art. 8P012100

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10"	12"
PN	20	20	20	20	20	20	20	20	20	10	10
ACT.	DA32	DA52	DA52	DA63	DA75	DA85	DA100	DA140	DA160	DA230	DA230
KIT	RI3518	RI3519	RI3520	RI3521	RI3522	RI3523	RI3552	RI3554	RI3554	RI4577	RI4577

*TRUNION $\Delta p=20$ Bar.



Art. 8P012200

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10"	12"
PN	20	20	20	20	20	20	20	20	20	10	10
ACT.	SR52	SR63	SR63	SR85	SR100	SR125	SR125	SR180	SR200	SR330	SR330
KIT	RI3519	RI3829	RI3525	RI3526	RI3522	RI3528	RI3528	RI3555	RI3555	RI4578	RI4578

*TRUNION $\Delta p=20$ Bar.

Art. 8E055***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10"	12"
PN	20	20	20	20	20	20	20	20	20	10	10
ACT.	VB015	VB015	VB030	VB060	VB060	VB110	VB190	VB350	-	-	-
KIT	RI3519	RI3519	RI3520	RI3521	RI4039	RI3523	RI3552	RI3553	-	-	-
12 V											
24 V											
100 - 240 V											



Art. 8M055***

With electric actuator series 86.


SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10"	12"
PN	-	-	20	20	20	20	20	20	20	10	10
ACT.	-	-	VB030M	VB060M	VB060M	VB110M	VB190M	VB350M	-	-	-
KIT	-	-	RI3520	RI3521	RI4039	RI3523	RI3552	RI3553	-	-	-
12 V											
24 V											
100 - 240 V											

VOLTAGE CODE

12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004
---------------------------	---------------------------	-----------------------------

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body type flanged ANSI 150 ball valve [Valpres art. 762000] carbon steel WCB, full bore, Fire Safe, Antistatic Device, face to face ANSI B16.10, classified ATEX Ex II 2 G/D c T3.



Art. 8P012300

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10" ^{TR}	12" ^{TR}
PN	20	20	20	20	20	20	20	20	20	10	10
ACT.	DA32	DA52	DA52	DA63	DA75	DA85	DA100	DA140	DA160	DA230	DA230
KIT	RI3518	RI3519	RI3520	RI3521	RI3522	RI3523	RI3552	RI3554	RI3554	RI4577	RI4577

^{TR}TRUNION $\Delta p=20$ Bar.



Art. 8P012400

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10" ^{TR}	12" ^{TR}
PN	20	20	20	20	20	20	20	20	20	10	10
ACT.	SR52	SR63	SR63	SR85	SR100	SR125	SR125	SR180	SR200	SR330	SR330
KIT	RI3519	RI3829	RI3525	RI3526	RI3522	RI3528	RI3528	RI3555	RI3555	RI4578	RI4578

^{TR}TRUNION $\Delta p=20$ Bar.



Art. 8E056***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10"	12"
PN	20	20	20	20	20	20	20	20	20	10	10
ACT.	VB015	VB015	VB030	VB060	VB060	VB110	VB190	VB350	-	-	-
KIT	RI3519	RI3519	RI3520	RI3521	RI4039	RI3523	RI3552	RI3553	-	-	-
12 V											
24 V											
100 - 240 V											

Art. 8M056***

With electric actuator series 86.


SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"	8"	10"	12"
PN	-	-	20	20	20	20	20	20	20	10	10
ACT.	-	-	VB030M	VB060M	VB060M	VB110M	VB190M	VB350M	-	-	-
KIT	-	-	RI3520	RI3521	RI4039	RI3523	RI3552	RI3553	-	-	-
12 V											
24 V											
100 - 240 V											

VOLTAGE CODE

12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004
---------------------------	---------------------------	-----------------------------

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body type flanged ANSI 300 ball valve [**Valpres art. 761030**] stainless steel AISI 316 CF8M, full bore, Fire Safe, Antistatic Device, face to face to ANSI B16.10, classified ATEX Ex II 2 G/D c T3.



Art. 8P021300

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	50	50
ACT.	DA52	DA63	DA63	DA75	DA85	DA100	DA115	DA180	DA200
KIT	RI3519	RI3829	RI3563	RI3526	RI3522	RI3552	RI3565	RI3555	RI3555

*TRUNION Δ p=25 Bar.



Art. 8P021400

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	50	50
ACT.	SR63	SR85	SR85	SR100	SR115	SR125	SR160	SR270	SR270
KIT	RI3829	RI3571	RI3573	RI4117	RI3527	RI3528	RI3997	RI3753	RI3753

*TRUNION Δ p=25 Bar.

Art. 8E111***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	-	-
ACT.	VB030	VB030	VB030	VB060	VB060	VB190	VB270	-	-
KIT	RI3519	RI3519	RI4116	RI3521	RI4039	RI3552	RI3565	-	-
12 V									
24 V									
100 - 240 V									



Art. 8M111***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	-	-
ACT.	VB030M	VB030M	VB030M	VB060M	VB060M	VB190M	VB270M	-	-
KIT	RI3519	RI3519	RI4116	RI3521	RI4039	RI3552	RI3565	-	-
12 V									
24 V									
100 - 240 V									

*** VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body type flanged ANSI 300 ball valve [Valpres art. 761031] carbon steel WCB, full bore, Fire Safe, Antistatic Device, face to face to ANSI B16.10, classified ATEX Ex II 2 G/D c T3.



Art. 8P021500

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	50	50
ACT.	DA52	DA63	DA63	DA75	DA85	DA100	DA115	DA180	DA200
KIT	RI3519	RI3829	RI3563	RI3526	RI3522	RI3552	RI3565	RI3555	RI3555

*TRUNION Δ p=25 Bar.



Art. 8P021600

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	50	50
ACT.	SR63	SR85	SR85	SR100	SR115	SR125	SR160	SR270	SR270
KIT	RI3829	RI3571	RI3573	RI4117	RI3527	RI3528	RI3997	RI3753	RI3753

*TRUNION Δ p=25 Bar.

Art. 8E112***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	-	-
ACT.	VB030	VB030	VB030	VB060	VB060	VB190	VB270	-	-
KIT	RI3519	RI3519	RI4116	RI3521	RI4039	RI3552	RI3565	-	-
12 V									
24 V									
100 - 240 V									



Art. 8M112***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"	6"	8"
PN	50	50	50	50	50	50	50	-	-
ACT.	VB030M	VB030M	VB030M	VB060M	VB060M	VB190M	VB270M	-	-
KIT	RI3519	RI3519	RI4116	RI4617	RI4039	RI3552	RI3565	-	-
12 V									
24 V									
100 - 240 V									

*** VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFLET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body full bore [Valpres art. 760150] flanged ball valve, ANSI 600 carbon steel A350-LF2, Fire Safe, Antistatic Device, ANSI B16.10.

Art. 8P027100

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"
PN	100	100	100	100	100	100	100
ACT.	DA52	DA52	DA63	DA85	DA85	DA125	DA140
KIT	RI3519	RI3519	RI3563	RI3526	RI3522	RI3565	RI3997





Art. 8P027200

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"
PN	100	100	100	100	100	100	100
ACT.	SR63	SR75	SR85	SR115	SR115	SR160	SR180
KIT	RI3829	RI3571	RI3573	RI4754	RI3527	RI3997	RI4755

PRODUCT LEAFET **2 WAY FLANGED VALVES WITH ACTUATOR**



 Split Body full bore [Valpres art. 760200] flanged ball valve, ANSI 600 stainless steel AISI 316, Fire Safe, Antistatic Device, ANSI B16.10.

Art. 8P027300

Con attuatore pneumatico doppio effetto serie 82.
With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"
PN	100	100	100	100	100	100	100
ACT.	DA52	DA52	DA63	DA85	DA85	DA125	DA140
KIT	RI3519	RI3519	RI3563	RI3526	RI3522	RI3565	RI3997




Art. 8P027400

Con attuatore pneumatico semplice effetto serie 82.
With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"	3"	4"
PN	100	100	100	100	100	100	100
ACT.	SR63	SR75	SR85	SR115	SR115	SR160	SR180
KIT	RI3829	RI3571	RI3573	RI4754	RI3527	RI3997	RI4755

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **full bore** [Valpres art. 68F000] flanged ball valve, ANSI 150, API standard 608, carbon steel LCB, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P080100

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8P080200

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8E213***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								



Art. 8M213***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								

***			VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004			

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **full bore** [Valpres art. 68F100] flanged ball valve, ANSI 300, API standard 608, carbon steel LCB, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P080500

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8P080600

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8E215***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								



Art. 8M215***

With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								

***			VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004			

PRODUCT LEAFET 2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR



Split Body **full bore** [Valpres art. 68F400] flanged ball valve, ANSI 600, API standard 608, carbon steel LCB, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P080900

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-



Art. 8P081000

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1 1/2"	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-



Art. 8E217***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1 1/2"	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-
12 V					
24 V					
100 - 240 V					



Art. 8M217***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1 1/2"	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-
12 V					
24 V					
100 - 240 V					

*** VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **full bore** [Valpres art. 68J000] flanged ball valve, ANSI 150, API standard 608, stainless steel CF8M, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P079900

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8P080000

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8E212***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								

Art. 8M212***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	20	20	20	20	20	20	20	20
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								

***			VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004			

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **full bore** [Valpres art. **68J100**] flanged ball valve, ANSI 300, API standard 608, stainless steel CF8M, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P080300

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8P080400

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-



Art. 8E214***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								



Art. 8M214 ***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1"1/2	2"	3"	4"	6"
PN	50	50	50	50	50	50	50	50
ACT.	-	-	-	-	-	-	-	-
KIT	-	-	-	-	-	-	-	-
12 V								
24 V								
100 - 240 V								

***			VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004			

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **full bore** [Valpres art. 68J401] flanged ball valve, ANSI 600, API standard 608, stainless steel CF8M, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P080700

With double acting pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-



Art. 8P080800

With spring return pneumatic actuator series 82.

SIZE	1/2"	3/4"	1"	1"1/2	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-



Art. 8E216***

With electric actuator series 85.

SIZE	1/2"	3/4"	1"	1"1/2	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-
12 V					
24 V					
100 - 240 V					



Art. 8M216***


With electric actuator series 86.

SIZE	1/2"	3/4"	1"	1"1/2	2"
PN	100	100	100	100	100
ACT.	-	-	-	-	-
KIT	-	-	-	-	-
12 V					
24 V					
100 - 240 V					

***			VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004			

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **reduced bore** [Valpres art. 68F000 PN20 - 68F100 PN50] flanged ball valve, ANSI 150 and ANSI 300, API standard 608, carbon steel LCB, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P080100

With double acting pneumatic actuator series 82.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-

Art. 8P080500



Art. 8P080200

With spring return pneumatic actuator series 82.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-

Art. 8P080600



Art. 8E213***

With electric actuator series 85.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

Art. 8E215***



Art. 8M213***

With electric actuator series 86.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			


SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

Art. 8M215***

*** VOLTAGE CODE		
12V AC/DC + 001	24V AC/DC + 002	100-240V AC + 004

PRODUCT LEAFET **2 WAY FLANGED VALVES API STANDARD 608 WITH ACTUATOR**



 Split Body **reduced bore** [Valpres art. **68J000 PN20 - 68J100 PN50**] flanged ball valve, ANSI 150 and ANSI 300, API standard 608, stainless steel CF8M, ASME B16.10 face to face dimension, Fire Safe, Antistatic Device.



Art. 8P079900

With double acting pneumatic actuator series 82.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-

Art. 8P080300



Art. 8P080000

With spring return pneumatic actuator series 82.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-

Art. 8P080400



Art. 8E212***

With electric actuator series 85.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

Art. 8E214***



Art. 8M212***

With electric actuator series 86.

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	20	20	20
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

SIZE	3" x 2"	4" x 3"	6" x 4"
PN	50	50	50
ACT.	-	-	-
KIT	-	-	-
12 V			
24 V			
100 - 240 V			

Art. 8M214***

***			VOLTAGE CODE		
12V AC/DC + 001		24V AC/DC + 002		100-240V AC + 004	



A.P.S. CONTROL CO., LTD., THAILAND

7 SOI ON-NUCH 62 SUKHUMVIT 77 RD. ON-NUCH SUANLUANG BANGKOK 10250 WWW.APSCONTROL.CO.TH

Tel: 0 2721 1800 (Auto) Fax: 0 2721 1791 E-mail: sales@apscontrol.co.th Line ID: aps.sales Tax.ID: 010-55430-20618

Note: We are engineering partner as a total system solution provider, VALBIA manufactures a range of components to ensure cost effective and reliable about quarter-turn actuators. As a comprehensive solution provider, We have great quality control procedures. The calculate various system designs and can work together perfectly. Finally we are fully committed to maintaining environment quality together.

VALBIA S.R.L., ITALY

Note: Only excellence allows to compete in the international market. The challenge can be faced thanks to the passion and the energy of the researchers, who plan and manufacture avant-garde quality and technology, a team which is perfectly integrated for providing total, customer satisfaction; we are ready!

To ensure the quality and technical standards at the highest level, the manufacturer reserves the right to alter the specifications without notice. This documentation supersedes and replaces all previous editions.

THE VALBIA BALL VALVE © 2019 Valbia. All Rights Reserved.