

Model		ER/M-02	ER/M-04	ER/M-10	EL/U-02	EL/U-04	EL/U-10	ESL/G-02	ESL/G-04	ESL/G-10
Humidity-ER/EL/ESL										
No humidity-EM/EU/EG										
Volume(L)		200	400	1000	200	400	1000	200	400	1000
P e r f o r m a n c e	Temperature range	-20~+150 °C			-40~+150 °C			-70~+150 °C		
	Humidity range	25~98%RH(20~85)								
	Temperature fluctuation	<0.5 (in accordance with GB/T5170.2-2008)								
	Temperature deviation	±2.0								
	Humidity deviation	±3.0%RH(>75%RH), ±5.0%RH(≤75%RH)								
	Heat-up rate	-20→+150			-40→+150			-70→+150		
		≤60min								
Pull-down rate	+20→-20			+20→-40			+20→-70			
	≤45min			≤45min		≤60min		≤80min		
Inside dimension (mm)	W	500	600	1000	500	600	1000	500	600	1000
	H	750	850	1000	750	850	1000	750	850	1000
	D	600	800	1000	600	800	1000	600	800	1000
Outside dimension (mm)	W	910	1010	1410	910	1010	1410	910	1010	1410
	H	1779	1879	2030	1779	1879	2030	1779	1879	2030
	D	1173	1373	1588	1173	1373	1588	1173	1373	1588
Power supply		380V (three phases and four wires+protective grounding wire)								
Condensing method		Air-cooled / Water-cooled								