

Rugged Handheld Data Terminal V5

Mobile Data Collection / IP64 Rating

Wireless Information Transfer / Powerful CPU / Dual OS



Highly ruggedized, flexible and easy to operate, UROVO's V5 handheld data terminal is designed for use in various industrial fields, including asset management, logistics, transportation, medicine safety supervision and production process management. Featuring dual OS (Windows CE or Android), 1GHz CPU, high-capacity battery and strong wireless communication ability including 3G, GPRS, WiFi and Bluetooth, this rugged terminal integrating with help you accomplish an array of industrial tasks efficiently in many areas.

Powerful Data Collection Ability

High speed data collection by 1D and 2D bar code scanner, RFID reader and IC card reader

Flexible and Adaptable

Ergonomic design for easy and comfortable operation, meeting IP64 environmental grade and supporting various industrial applications

Wireless Communication

Supports GPRS/GSM, 3G, WLAN, Bluetooth and other communication modes according to project requirements

Multiple Data Interfaces

Provides USB & RS232 interfaces and supports voice communication

Strong Data Storage

Built-in large RAM/ROM capacity, supports extended Micro SD/TF card (up to a maximum of 32GB capacity supportable)

Dual-system Supportable

Supports Windows CE 6.0 & Android 2.3 operating systems, provides SDK for secondary development on different applications



Application Fields:

Transportation & Logistics / Garment & Chain Store / Retail Market / Retail & Wholesale
International Trade / Healthcare & Hospitality / E-commerce / Production Management
Government Law Enforcement / Manufacturing

UROVO V5 Specification

Physical Characteristics	Dimensions	Max: 190mm*75mm*30mm/Hand Grip: 90mm*60mm*25mm	
	Weight	350g (including battery)	
	Display	3.5inch TFT-LCD QVGA (240×320)/VGA (480×640) color touch screen	
	Keyboard	33 keys (numeric/alphabetic keys, directional button, scan button, side keypad)	
	Input	Chinese, English, Handwriting, support soft keyboard	
	Power	Main Battery	Removable, rechargeable 3.7V 3000mAh lithium battery pack Over 8 hours of standby time (depending on the specific environment)
Performance Characteristics	CPU	Slave Battery	150mAh lithium battery
		RTC Battery	Individual RTC to keep clock at real time
	O.S.	Microsoft Windows CE 6.0 R3 & Android 2.3 (multi-language)	
	Memory	ROM	256MB/512MB Nand Flash
	Expansion	RAM	256MB/512MB Mobile DDR
		Support Micro SD/TF up to 16G, SIM x 1	
Barcode Scanner	Audio	Loudspeaker x 1, microphone x 1, earphone x 1	
	Interfaces	Mini USB x 1, 3.5mm audio jack x 1	
	1D Laser	Scanning Rate	100±20 scan/sec
		Decode Capability	Code 39; Codabar; Code 128; Discrete 2 of 5; IATA 2 of 5; Interleaved 2 of 5; Code 93; UPC A; UPC E0; EAN 8; EAN 13; MSI; EAN 128; UPC E1; Trioptic Code 39; Bookland EAN; Coupon Code; RSS-Limited; RSS-14; RSS-Expanded
	2D CMOS	1D Symbolologies: UPC/EAN, Bookland EAN, UCC Coupon Code, ESSN EAN, CODE 39, CODE 128, GS1-128, ISBT 128, Trioptic Code 39, CODABAR, MSI, Interleaved 2/5, Discrete 2/5, Chinese 2/5, Korean 3/5, Matrix 2/5, CODE 32, CODE 93, CODE 11, Inverse 1D, GS1 DataBar, Composite Codes	
		2D Symbolologies: PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, MaxiCode, QR Code, Aztec, Aztec InversePostal Codes: U.S. Postnet, U.S. Planet, U.K. Postal, Japan Postal, Australian Postal, Netherlands KIX Code, USPS 4CB/One Code/Intelligent Mail, UPU FICS Postal	
Radio Communication	Wireless LAN	WiFi 802.11b/g; frequency range: 54MB/sec; CISCO Compatible CCX2/3 Security, CISCO AP Security	
	WAN	Frequency Range	GSM 850/900/1800/1900MHz
		Data Rate	GPRS multi-slot Class 10: DL 85.6 kbps/UL 42.8 kbps GPRS multi-slot Class 8: DL 85.6 kbps/UL 21.4 kbps
	WCDMA	Frequency Range	UMTS2100/900MHz UMTS1900/850MHz GSM850/900/1800/1900MHz
		Data Rate	GSM CS: UL 9.6kbps/DL 9.6kbps GPRS/EDGE: Multi-slot Class 12, Class B WCDMA CS: UL 64kbps/DL 64kbps WCDMA PS: UL 384kbps/DL 384kbps HSDPA: DL 3.6Mbps
		Frequency Range	CDMA2000 1X, CDMA2000 EV-DO Rev 0, CDMA2000 EV-DO Rev A Supports BC0 (800MHz), BC1 (1900MHz)
		Data Rate	CDMA2000 1X: UL/DL: 153.6kbps CDMA2000 1X/EVDO Rev.0: UL 153.6 kbps DL 2.4 Mbps CDMA2000 1X/EVDO Rev A: UL 1.8 Mbps DL 3.1 Mbps
	Bluetooth	Bluetooth Class2.1+EDR	
	Camera	3.0/5.0 mega pixels with flash light, screen capture and automatic focus	
	GPS	Support A-GPS, 48 channels; accuracy<1m; 1sec wakeup, warm bootup less than 38sec	
Options	RFID	Customizable, support: LF: ISO11784/11785 HF: ISO15693, ISO14443A/B, SRI513/SRI4KU HF: ISO180006B (EPC C1 Gen2), ISO18000-6C	
	Operating	-10°C to +50°C	
	Storage	-20°C to +60°C	
	Humidity	5% to 95% non condensing (condensation resistant configurations available)	
	Drop	Multiple drops to concrete: 5ft./1.5m across the operating temperature range	
Peripherals and Accessories	Sealing	IP64 standard for water and dust resistance	
	Cradle	Double-slot serial/USB	
	Printer	Supports extensive line of Bluetooth SPP approved printers and cables	
	Charger	4-slot universal battery charger	
	Other Accesories	USB cradle cable	
Regulatory	Product Certification	CCC, CE, FCC	
	Electrical Safety	Certified to UL60950, CSA C22.2 No.6050, EN60950/IEC950	
	Laser Safety	IEC Class 2/FDA Class II, in accordance with IEC60825-/EN60825-1	
	Warranty	12 months (except for accessories)	

Authorized Distributor



**Computer Peripheral
and Supplies Ltd.**

244 Soi Pattanakarn 53, Suanluang, Suanluang, Bangkok 10250 Thailand
Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990
www.cps.co.th • www.facebook.com/cps.co.th

