


Item #		Thermal Printer RP332
Photo		
		USB+SERIAL+ETHERNET
Color		Black
Print	Printing Method	Thermal Line
	Printing Speed	250mm/s
	Resolution	203dpi
	Effective Printing Width	72mm & 48mm
Character	Character Set	ANK,GB18030(Chinese)
	Print Font	ANK: 12 x24,9x17, Chinese: 24 x 24
	Character per Line	48-font A/64-font B
Paper Spec	Paper Type	Thermal paper
	Paper Width	80mm & 58mm
	Paper Roll Diameter	Max: 80.0mm
Paper Supply Method		Drop-in paper load
Reliability	MCBF	60 million lines
	Auto Cutter	2 million cuts
	TPH	150km
Barcodes	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93,	
Emulation		ESC/POS
Driver		XP, Win7, Win8, Win10, iOS, Android, Linux, MacOS
Sensor		Paper End Sensor, Paper Near End Sensor(Optional)
Drawer Port		RJ11
Interface		USB/SERIAL/ETHERNET
Network	Wire	TCP/IP Ethernet interface (10M/100M)
Power Supply (Adapter)		AC100 ~240V(± 10%) DC 24V, 2.5A
Auto cutter	Type	straight knife
	Life	2,000,000 cuts
Physical	Printer Dimension	215*148*145mm
Environment parameters:		Working temperature: -20 °C—70 °C Working humidity: 0 °C —40 °C Storing temperature : 5%—95% Storing humidity:20%—85%
Application	Restaurant, Department Store, Kitchen, Convenience Store, Specialty Retail, Super	

