

A620

SmartMobile Terminal

Powered by Android 6.0 | High Capacity Battery | 5-inch IPS Touchscreen | Reads 1D/2D Codes | Supports Extension Base | Suitable for Complicated Dining Environment



Powered by Android

PAX A620 is a smart mobile terminal powered by Android 6.0. Rocking a quad-core ARM processor and a 5-inch HD touchscreen, the multi-function A620 is able to work consistently at peak performance.

Simple and secure development environment, packed with applications, supports 4G, Wi-Fi, Bluetooth and many other communication methods; Build-in professional HD code scanning camera, offers exceptional code recognition

capability; Massive storage, supports Micro SD card and multi-media function; Double high capacity Li-ion Battery, allows for sustained operation during peak hours.

The A620 uses double color injection molding and is designed with ergonomic care, its slim and compact body is perfectly comfortable for handling on the move. Our A620 smart mobile terminal will certainly shine bright in the new smart payment environment.

FEATURES & BENEFITS

Multi-Functional Terminal

- o Rear Camera Design, Reads 1D / 2D codes
- o Supports Application Whitelist / Blacklist
- o 4G, Wi-Fi, Bluetooth Connectivity
- o 5-inch HD IPS Touchscreen
- o Supports Extension Base
- o ThermalPrinter

Exceptional Performance

- o Powered by Android 6.0
- o Supports Micro SD card
- o High Capacity Battery
- o Quad-Core Processor
- o 1GB RAM



A620

SmartMobile Terminal

SPECIFICATIONS

OS	PayDroid Powered by Android 6.0
Processor	Application CPU: Quad-core Cortex-A7, 1.3GHz
Memory	1GB DDR + 8GB eMMC 1 x Micro SD Card Slot, Supports up to 128GB
Camera	2 Megapixel Rear Camera with LED Flashlight Reads 1D & 2D Codes
Display	5-inch All Perspective IPS Display 1280 x 720Pixels Multi-Point Capacitive Touchscreen
Audio	1 x Speaker
Physical Button	1 x ON/OFF button 2 x Volume +/- button
Communications	Wi-Fi 2.4G, Supports Hotspot 4G (FDD-LTE / TDD-LTE) + 3G (WCDMA) + 2G (GSM / GPRS) Bluetooth 4.0
Card Slots	1 x SIM
Peripheral Ports	1 x USB Type-C 1 x 3.5mm Audio Jack
Printer	2-inch Thermal Printer Print Speed: 80mm/s Paper Width: 58mm Paper Diameter: 40mm
Battery	7.2V / 2600mAh Rechargeable Li-ion Battery
Adapter	Input: 100 - 240V AC, 50Hz / 60Hz 0.4A Output: 5.0V DC, 2.0A
Sensor	G-Sensor (optional)
Location	GPS GLONASS BEIDOU
Accessories	Charging Base(optional) Multifunctional Base (optional)
Indicators	Charging indicator
Physical	L x W x H (mm) : 185.2 x 80.6 x 71.5 Weight (g) : 400 (including battery)
Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 90% Relative Humidity, Non-Condensing
Certifications	CE RoHs

