





Quotation Sheet of Impact Printer

Item #		24 pins Impact Printer RP835
Photo		 
Print	Product type	Impact Printer
	Printing method	Dot matrix impact printing
	Print direction	Duplexing logic
	Pins number	24 pins
	Printing head working life	400 million characters /pin
	Ribbon type	S010076/S010058, S015583/S015290
	Ribbon working life	4 million chars/letter model, 8 million chars/cursive model
	Copy ability	1 original + 6 copies
	Buffer	1M (SDRAM)
	Interface	USB2.0, IEEE-1284, Bluetooth (For Bluetooth Model)
Property	Resolution	Letter mode:360x120dpi
	Character repertoire	GB18030 & ASCII, and will add 14 kind of characters in follow, USA、France、Germany、UK、Denmark I、Sweden、Italy、Spain I、Japan、Norway、Denmark II、Spain II、Latin America、Korea、Legal
	Typeface	Epson Draft, Epson Roman, Epson Sans Serif, Epson OCR-B
	Scalable typeface	4 types
	Barcode	8 types
	Control code	ESC/P-K, IBM PPDS, OK15530SC
	Printing speed	Chinese(6.7cpi): Max 173 chars/sec, normal 115 chars/sec, letter model 57 chars/sec
		Chinese(7.5cpi): Max 195 chars/sec, normal 130 chars/sec, letter model 65 chars/sec
		English(10cpi): Max 347 chars/sec, normal 260 chars/sec, letter model 86 chars/sec
		English(12cpi): Max 416 chars/sec, normal 312 chars/sec, letter model 103 chars/sec
English(15cpi) Max 521 chars/sec, normal 390 chars/sec, letter model 129 chars/sec		
Reliability	20 million lines	

Medium	Paper in method	friction feed(in front), sprocket feed(backside)
	Paper type	single-sheet, copy paper, continuous paper, envelope, postcard, continuous
	Paper width	single-sheet paper: 70-257mm, continuous paper: 76.2-254mm
	Paper thickness	0.052-0.53mm
Dimension (LxWxH)		385×307×188mm
Weight		3.8kg
MTBF		10000 hours
Support		Windows 2000/XP/Vista/win7
Operation Voltage		AC 220-240V, 50/60Hz
Noise		56dB under ISO7779 model
Environment	Working	5-35 °C /10-80%RH
	Storage Temperature/Humidity	-30-60 °C /0-85%



**Computer Peripheral
and Supplies Ltd.**

244 Soi Pattanakarn 53, Suanluang, Suanluang, Bangkok 10250 Thailand
Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990
www.cps.co.th • www.facebook.com/cps.co.th

