



PRINT NOW. PRINT MORE. High-Speed Retransfer Card Printer



New Trusted Identity Begins

SOLID-810 is a new generation retransfer card printer that offers the fastest issuance speed in the industry. IDP's innovative retransfer heating technology- **Rapid Retransfer Printing** technology or "RRP" provides the fastest "Ready to Print" metric in the industry. No more waiting several minutes for your out-dated retransfer printer to heat up.

RRP technology from IDP offers power-on and Ready to Print in only seconds. The SOLID-810 produces higher-quality, sharper-looking images than traditional card printers. It is the perfect choice for demanding applications which require deep dark colors with infinity-edge (full-bleed) graphics on blank or technology cards.

The input card hopper holds up to 200 cards and physical security features allow you to easily secure your printer, its supplies, and ejected cards in instant bank-card issuance or high-security applications.





High Volume Capacity



Infinity Edge Printing Quality

PRINT NOW. PRINT MORE. Still waiting for printer boot-up?

No more waiting, save your precious time - SOLID-810 gives you the fastest issuance speed and allows you to experience simultaneously power-on and print in only seconds unlike the traditional retransfer card printers which take several minutes.

Innovative retransfer head heating control technology creates more sharp-looking images and text quality every time.

Perfect printing on embedded chip cards - SOLID-810 can print graphical card design right to the edges even on smart cards with uneven surfaces.

It's the ideal choice for customers that demand more functionality and high security such as government, bank, education, and healthcare.

Innovative Retransfer Head Heating Control - Heat up & Print ready in only seconds

Glossy, Superior high resolution

Intelligent Anti-dust circulation

Complies with International Banking Instant Issuance Security Standards

- Physical & Electronic Locking system
- Secured bolt-down fixture







Stress-free Anti-dust circulation

Advanced Security Compliant Robust & Innovative Product design

FORGET ABOUT DUST & THEFT. Extend your card printer life

Intelligent anti-dust circulation - Designed with fine dust filter and disposable cleaning roller to help flawless printing quality by removing dust and other particles.

An Intelligent air circulation structure effectively controls the temperature in the printer during continuous card issuance.

Advance security compliant -SOLID-810 prevents theft and counterfeiting of sensitive financial resources.

It is equipped with a physical and electronic locking integration system that complies with the *International Banking Instant Issuance Security Standards*.

Additionally, a secured bolt-down fixture supports high-level security ID card demands.





SPECIFICATIONS

Model		SOLID-810S	SOLID-810D	RIBBONS		
Printing	Print Type		Dye-Sublimation / Resin Thermal Retransfer		500 Cards/Roll	Full Color Ribbon with Resin Black
	Print Area	Single-Sided Infinity-edge / Full Bleed	Dual-Sided Infinity-edge / Full Bleed	YMCKK	500 Cards/Roll	Full Color Ribbon with Resin Black & Resin Black for Back Side
Card	Resolution	300dpi				Resin Black for Back old
	Card Feeding	Automatic				
	Card Size	ISO CR80 (54mm x 86mm / 2.12" x 3.38")		RETRANSFE	REILM	
	Card Thickness	0.76mm (30mil) ~ 1.6mm (64mil)		Retransfer Film		500 Cards/Roll
	Card Type	PVC, PC, PET, Composite PVC		· ·		
Print Speed	Single Side	Max. 25 sec./card (144 cards/hour)	Max. 25 sec./card (144 cards/hour)			
	Dual Side		Max. 43 sec./card (84 cards/hour)			
Capacity	Input Hopper	200 Cards		RIBBON & FILM PACKAGE YMCK & Retransfer Film 500 Cards/Each Roll		Full Color Ribbon with Resin Black & Retransfer Film
	Output Hopper	100 Cards				
	Error card bin	25 Cards		·		Returnater Film
System	Memory	128MB RAM				
	Display & Control Panel	2 Line Graphic LCD Indicator / 4 Buttons				
	Supported Platforms	Microsoft Windows 7/8/10/11, Mac OS, Linux				
	Communication	USB, Ethernet			14	
	Power Supply / Consumption	100-240V~ 50/60Hz 2.5A		100	,	
	Temperature / Humidity	15~35°C / 35~70%				310
Dimensions	WxDxH (Millimeter / Inch)	460 x 224 x 310 / 18.1 x 8.8 x 12.2			SOLID	(12.2
	Kg/lbs	11.4/25.13			ABIÒ	
Options	Encoding	Magnetic stripes : ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo) Contact : ISO 7816 (ID-1) / Contactiess : ISO 14443 (Type A/ B), ISO 18092(INFC), MIFARE, DESFIRE		7	460 mm (18.1 lnch)	224 mm (8
	WiFi	IEEE 802.11 a/ b/ g/ n				/
	Security	Physical & Electronic Locking System				

- Print Speed : May change under specific condition.





244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990 www.cps.co.th • www.facebook.com/cps.co.th

CONSUMABLES

