

Datasheet FUJITSU Image Scanner fi-800R

Compact and versatile scanner for the front office



The FUJITSU fi-800R is a compact yet highly efficient document scanner capable of scanning all types of documents including passports and IDs. It includes robust features such as reverse feeding and Active Skew Correction---an industry first! --all to provide an agile and efficient scanning experience on even the most crowded of desks. Because of its U-turn feeder and elimination of the paper exit tray, the fi-800R fits into tight spaces and eliminates the need for multiple scanning devices

The fi-800R scans A4 portrait documents at comfortable speeds of 40 ppm/80 ipm (200/300 dpi) and makes customer onboarding easy with its compact size and versatile scanning abilities.

Ultra compact footprint for limited spaces

The fi-800R is the perfect scanner when space is limited. Designed to fit in tight office spaces, it comes equipped with the Dual Path Mechanism, enabling scanning of a wider variety of documents. Satisfy all your scanning needs, from plastic cards to booklets, with a single device.

Versatile scanning functionalities U-turn Scan using the ADF makes the small footprint even smaller. The stacker extends to provide neatly stacked output documents and returns to its original position once scanning has completed, so that users can easily start scanning their next batch.

Clever ID scanning for a quick customer onboarding process

Using Return Scan, scan passports and ID up to 5 mm thick without using a carrier sheet. Simple one sheet scanning also no longer requires the hassle of opening the feeder. Clever operation and fast scanning speeds of a mere 3.5 seconds reduce customer wait times and help provide great customer experiences.

Stress-free operation with accurate paper feeding performance

Serve customers faster with the fi-800R's robust feeding functionalities. With Automatic Skew Correction, documents are straightened one sheet at a time for precise paper feeding. Active Separation also adjusts pressure to ensure each sheet is separated and captured without any misfeeds. Confidently scan mixed batches and make customer onboarding more efficient.

Advanced software for maximized efficiency

Empower reception workflows and use information more efficiently with our enhanced PaperStream IP scanner driver and integrated PaperStream Capture software. With the MRZ Recognition function, the Machine Readable Zone on passports are recognized and extracted as metadata for fast client retrieval. Users no longer need to organize documents or check if documents with photo IDs are scanned face up, since the Front Side Detection function detects photos on ID cards and passports to automatically set pages with photos as the front side. With a few simple setting configurations, Automatic Profile Selection also allows documents to undergo image processing appropriate to each document format. All these functionalities work together to offer a wider variety of batch scanning features and make employees more efficient.

Technical Information

Scanner Type Scanning Speed*1 (A4 (Color*2/Grayscale*2/M Image Sensor Type Light Source Optical Resolution* Output Resolution* Output Resolution* Output Format Background Colors Document Size Maximum Minimum Long Page Scanning* Paper Weight (Thickne ADF Paper Manual Feed Paper	Aonochrome*3)	ADF Manual Feed CIS x 2 (front x RGB LED (front 600 dpi 50 to 600 dpi (1,200 dpi (drive	x 1, back x 1) adjustable by 1 dpi increments)	Operating Environment Temperature Relative Humidity Environmental Complian Dimensions* ⁹ (Width x Depth x Height Weight Supported Operating Sys	20 to nce ENERG t) 296 x 2.0 kg stem Window	5 °C (41 to 95 °F) 80% (non-condensing) 5Y STAR®, RoHS 105 x 83 mm (11.7 x 4.1 x 3.3 in.) 1 (4.4 lb)	
(Color*2/Grayscale*2/M Image Sensor Type Light Source Optical Resolution Output Resolution*4 (Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Minimum Long Page Scanning*6 Paper Weight (Thickne ADF Paper	Aonochrome*3)	Manual Feed CIS x 2 (front x RGB LED (front 600 dpi 50 to 600 dpi (1,200 dpi (drive Color: 24-bit, G bit	Duplex: 80 ipm (200/300 dpi) 3.5 seconds (200/300 dpi) 1, back x 1) x 1, back x 1) adjustable by 1 dpi increments) er) *5	Relative Humidity Environmental Complian Dimensions* ⁹ (Width x Depth x Height Weight	20 to nce ENERG t) 296 x 2.0 kg stem Window	80% (non-condensing) GY STAR®, RoHS 105 x 83 mm (11.7 x 4.1 x 3.3 in.) (4.4 lb)	
Image Sensor Type Light Source Optical Resolution Output Resolution** (Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Long Page Scanning** ADF Paper		CIS x 2 (front x RGB LED (front 600 dpi 50 to 600 dpi (r 1,200 dpi (drive Color: 24-bit, G bit	3.5 seconds (200/300 dpi) 1, back x 1) x 1, back x 1) adjustable by 1 dpi increments) er) *5	Environmental Complian Dimensions ^{*9} (Width x Depth x Height Weight	nce ENERG t) 296 x 2.0 kg stem Window	5Y STAR®, RoHS 105 x 83 mm (11.7 x 4.1 x 3.3 in.) (4.4 lb)	
Light Source Optical Resolution Output Resolution** (Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Minimum Long Page Scanning** Paper Weight (Thickne ADF Paper	onochrome)	RGB LED (front 600 dpi 50 to 600 dpi (1,200 dpi (drive Color: 24-bit, G bit	x 1, back x 1) adjustable by 1 dpi increments) er)* ⁵	Dimensions*9 (Width x Depth x Height Weight	t) 296 x 2.0 kg stem Windov	105 x 83 mm (11.7 x 4.1 x 3.3 in.) (4.4 lb)	
Optical Resolution Output Resolution** (Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Long Page Scanning** Paper Weight (Thickne ADF Paper	onochrome)	600 dpi 50 to 600 dpi (1,200 dpi (drive Color: 24-bit, G bit	adjustable by 1 dpi increments) er)* ⁵	(Width x Depth x Heigh Weight	2.0 kg stem Window	(4.4 lb)	
Output Resolution** (Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Long Page Scanning*6 Paper Weight (Thickne ADF Paper	onochrome)	50 to 600 dpi (1,200 dpi (drive Color: 24-bit, G bit	er)* ⁵	Weight	2.0 kg stem Window	(4.4 lb)	
(Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Minimum Long Page Scanning*6 Paper Weight (Thickne ADF Paper	onochrome)	1,200 dpi (drive Color: 24-bit, G bit	er)* ⁵		stem Window		
(Color / Grayscale / Mo Output Format Background Colors Document Size Maximum Minimum Long Page Scanning*6 Paper Weight (Thickne ADF Paper	onochrome)	1,200 dpi (drive Color: 24-bit, G bit	er)* ⁵	Supported Operating Sys	WINDOW	we 10 Windowe 0 1 Windowe 7 Windowe Come	
Background Colors Document Size Maximum Minimum Long Page Scanning*6 Paper Weight (Thickne ADF Paper		bit	rayscale: 8-bit, Monochrome: 1-		Supported Operating System Windows® 10, Windows® 8.1, Windows® 7, Windows Server		
Document Size Maximum Minimum Long Page Scanning*6 Paper Weight (Thickne ADF Paper		White		N		2019, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008 R2, Windows Server® 2008	
Maximum Minimum Long Page Scanning* ⁶ Paper Weight (Thickne ADF Paper		White		Included Software / Driv	ers PaperS	PaperStream IP driver (TWAIN/TWAIN x64/ISIS), WIA	
Minimum Long Page Scanning* ⁶ Paper Weight (Thickne ADF Paper						¹⁰ , PaperStream Capture, Software Operation Panel, ecovery Guide, ABBYY FineReader for ScanSnap™*11,	
Long Page Scanning** Paper Weight (Thickne ADF Paper	Maximum		nm (8.5 x 14 in.)		Scanne	Scanner Central Admin	
Paper Weight (Thickne ADF Paper	Minimum		n (2 x 2 in.)	Image Processing Funct	Image Processing Functions Multi image output, Automatic color detection, Blank pa detection, Static threshold, Dynamic threshold (iDTC),		
ADF Paper	6	5,588 mm (220) in.)		Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/Blue/White/		
	ess)				croppir	tion/Custom), sRGB output, Cropping, Index tab 19, Split image, De-Skew, Edge correction, Vertical	
Manual Feed Paper	r	40 to 127 g/m ² (11 to 34 lb) For A6 or smaller: 40 to 209 g/m ² (11 to 56 lb)		streaks reduction, Character extraction, Background pattern removal			
Manual Feed Paper		For A8 or smaller: 127 to 209 g/m² (34 to 56 lb) 20 to 413 g/m² (5.4 to 110 lb)		Included Items AC cable, AC adapter, USB cable, Setup DVD-ROM			
Plastic	c Card	1.4 mm or less					
Bookle	et	5 mm or less		Options			
ADF Capacity*7		20 sheets (A4 80 g/m² or Letter 20 lb), 30 sheets (A4 52 g/m² or Letter 14 lb)		Carrier Sheets	PA03360-0013	Each package contains 5 carrier sheets	
Expected Daily Volume* ⁸		4,500 sheets		Photo Carrier Sheets	PA03770-0015	Each package contains 3 carrier sheets	
Multifeed Detection			on (Ultrasonic sensor)	Booklet Carrier Sheet	PA03795-0018	Each package contains 1 carrier sheet	
		•		Space Savings USB (90	CG01000-29760	Save 2 inches of space in scanner width	
Interface		USB 3.2 Gen 1x	1 / USB 2.0 / USB 1.1	Degree)	cco1000 20770		
Power Requirements		AC 100 to 240	/ ± 10%	Reverse Path Stacker	CG01000-29770	I Saves operational space. Can place the scanner directly against the wall	
Power Consumption							
Operating Mode		19 W or less		Consumables			
Sleep Mode		1.7 W or less		Pick Roller	PA03795-0001	Every 150,000 sheets or one year	
Auto Standby (Off) Mode		0.15 W or less		Pad Unit	PA03795-0002	Every 30,000 sheets or one year	

*1 Actual scanning speeds are affected by data transmission and software processing times. *2 Indicated speeds are from using JPEG compression. *3 Indicated speeds are from using TIFF CCITT Group 4 compression. *4 When scanning in high resolutions (500 dpi or above), scanning may be rejected depending on scanning mode, document size, memory size, and application program. Selectable maximum density may vary depending on the length of the scanned document. *5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *6 Long page scanning is only available when using the ADF. Supports documents with lengths of up to 5,588 mm (220 in.) when resolutions are set to 200 dpi or less. For higher resolutions, supported document lengths vary. *7 Maximum capacity depends on paper weight and may vary. *8 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. *9 With the ADF paper chute closed. *10 Functions equivalent to those offered by PaperStream IP may not be available with the WIA Driver. *11 Software can be downloaded from the website designated in the Setup DVD-ROM.

Trademarks

ISIS is a trademark of Open Text. QR code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies. Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings. ENERGY STAR®

PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Specifications are subject to change without notice. Visit the fi Series website for more information. http://us.fujitsu.com/fcpa

Page 2 of 2

© Fujitsu 2019 2019.10 800R-1.0



244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990 www.cps.co.th • www.facebook.com/cps.co.th

