



The most productive large-format color MFP<sup>1</sup>—prints up to size E/A0



# All your workflow needs in a highproductivity MFP

- Create D/A1-size pages in 21 seconds on the market's fastest, compact 36-inch MFP1
- Achieve dark blacks, true neutral grays, and vivid colors with Original HP inks
- Print out your first page right away thanks to ultra-fast processing and zero warm-up time
- Copy and scan quickly with advanced features—presets, batch scanning, multipage PDFs, and scan to email

# A production printer for unattended, low-cost use

- Print your black-and-white drawings at the same cost per page as comparable black-and-white LED MFPs2
- Operate unattended thanks to two heavy rolls of up to 650 ft (200 m) and a total ink capacity of 1,800 ml
- Built for high-volume printing—rely on a robust design to fulfill the most demanding jobs
- Manage projects and control costs effectively, using embedded professional accounting features

# **End-to-end workflow efficiency**

- Stay organized and avoid clutter—the integrated 100-page stacker delivers prints and copies neatly collated
- Manage PDFs, increase production, and cut job preparation time by up to 50% with HP SmartStream for DesignJet printers<sup>3</sup>
- HP Crystal Preview<sup>4</sup> from HP SmartStream for DesignJet printers accurately shows how technical documents will be printed



#### **Eco Highlights**

- Half the energy consumption per plot than equivalent black-and-white LED MFPs
- ENERGY STAR® qualified and EPEAT Bronze registered²
- Free, convenient HP ink cartridge and printhead recycling<sup>3</sup>
- FSC®-certified papers and a range of recyclable HP media with a take-back program





- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per minute
- Compared with range-normal cow volunt actions reached the EDPATS within Spects of up or Arthor to page per limited.

  PEPAT registered where applicable and/or supported. See epeat.net for registration status by country.

  Program availability varies. Please check hp. com/recycle for details. BMG trademark license code FSC\*-C115319, see fsc.org.

  HP trademark license code FSC\*-C017543, see fsc.org. Not all FSC\*-certified products are available in all regions. For information about HP large format printing materials, please visit globalBMG.com/hp.

Find out how at our website



- 1. With Aurasma installed, please go to the HP DesignJet channel at http://auras.ma/s/ke25m
- 2. Without Aurasma installed, please download it:
  - a. Google Play http://auras.ma/s/android
  - b. Apple Store http://auras.ma/s/ios
  - Once done, go to the HP DesignJet channel at http://auras.ma/s/ke25m
- 3. Open the application and point to the image to view the HP DesignJet video

### **Technical specifications**

Print	Line drawings <sup>5</sup>	21 sec/page on A1/D, 120 A1/D prints per hour
	Print resolution	Up to 2400 x 1200 optimized dpi
	Margins (top x	Roll: 3 x 3 x 3 x 3 mm (0.12 x 0.12 x 0.12 x 0.12 in) (borderless on
	bottom x left x right)	photo papers) Sheet: 3 x 22 x 3 x 3 mm (0.12 x 0.87 x 0.12 x 0.12 in)
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
	Ink cartridges	6 (cyan, gray, magenta, matte black, photo black, yellow)
	Line accuracy	+/- 0.1% <sup>6</sup>
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
	Guaranteed	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) <sup>7</sup>
	minimum line width	
Media	Handling	Input: two automatic front-loading roll feeds; smart roll switching; rolls up to 200 m (650 ft) long each and 180 mm (7.1 in) of diameter; sheet feed
		Output: integrated output stacker (from A4/A to A0/E, with up to 100 A1/D-size capacity); media bin; automatic cutter Scanner: straight-through scan paper path for sheet and cardboard originals
	Size	Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)
	Thickness	Up to 0.5 mm (19.7 mil)
Scan	Scan speed	Color: up to 6.35 cm/sec (2.5 in/sec)
	- ·	Grayscale: up to 19.05 cm/sec (7.5 in/sec)
	Scan/ copy resolution	Up to 600 dpi
	Maximum scan	Size: 914 x 8000 mm (36 x 315 in) (JPEG)
		914 x 5000 mm (36 x 197 in) (PDF) 610 x 15,000 mm (24 x 590.5 in) (TIFF)
	Thickness	Up to 0.8 mm (0.03 in)
Сору	Reduction/	25 to 400%; at 1% increment
· <del>-</del>	enlargement	
	Maximum copies	Up to 99 copies
	Copier settings	Copy quality, copy color, roll, paper output, content type, original pape
		type, background removal, contrast, de-skew, blueprints support, copy margin layout, full width, job queue storage mode
Applications	Line drawings Pond	erings, Presentations, Maps, Orthophotos
Memory		processor, 128 GB (virtual),® 500 GB hard disk (AES-256 encrypted, FIPS
r-telliol y	140-2 Level 2 certifi	
Connectivity	Interfaces	High-Speed USB 2.0 certified host connector
	(standard)	Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IR, BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4o only), SMP (v1 v2c, v3), Apple Bonjour Compatible, FTP, W5 Discovery, Embedded Web Server(HTTP, HTTPs), IPSec, SMTP (e-mail), Raw IP printing (9100, 9101, 9102), LPD, IPP, WS print, NTLM, NTLM v2, SSL/TLS, 802.1X authentication (WEP, WPA, WPA2, LEAP, PEAP, EAP-TLS)
	Print languages	HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI
	(standard)	
	Print languages (optional)	Adobe PostScript 3; Adobe PDF 1.7
	Printing paths	email printing
		driver, HP Embedded Web Server, direct printing from USB flash drive, email printing
	Drivers (included)	driver, HP Embedded Web Server, direct printing from USB flash drive,
	Drivers (included)  Printer	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in)
(w x d x h)	Drivers (included)  Printer Shipping	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac 05 $\times$ ; PostScript Windows and Mac drivers with optional PostScript/PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) $1400 \times 784 \times 1109 \text{ mm} (55.1 \times 30.9 \times 43.7 \text{ in})$ $1502 \times 780.5 \times 804 \text{ mm} (59.1 \times 30.7 \times 31.7 \text{ in})$
(w x d x h)	Drivers (included)  Printer Shipping Printer	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in)
Dimensions (w x d x h) Weight	Printer Shipping Printer Shipping	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS $x$ ; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) $1400 \times 784 \times 1109 \text{ mm} (55.1 \times 30.9 \times 43.7 \text{ in})$ $1502 \times 780.5 \times 804 \text{ mm} (59.1 \times 30.7 \times 31.7 \text{ in})$ $114 \text{ kg} (251 \text{ lb})$ $141 \text{ kg} (310.8 \text{ lb})$
(w x d x h)	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in
(w x d x h)  Weight  What's in the box  Environmental	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP Designate Universal Print Driver for HP-GL/2 and HP Designate Universal Print Driver for HP-GL/2 and HP Designate Universal Print Driver for PS (with PostScript/PDF Upgrade Kit)  1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in)  141 kg (251 lb)  141 kg (310.8 lb)  Production Multifunction Printer, printhead, introductory ink
(w x d x h) Weight What's in the box	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)
(w x d x h)  Weight  What's in the box  Environmental	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 140 kg (310.8 lb) 140 kg (310.8 lb) 141 kg (310.8
(w x d x h)  Weight  What's in the box  Environmental	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)
(w x d x h) Weight What's in the box Environmental ranges	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, spindle adapter kit (s) Operating temperature Storage temperature	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 142 kg (310.8 lb) 143 kg (310.8 lb) 144 kg (310.8 lb) 145 kg (310.8 lb) 146 kg (310.8 lb) 147 kg (310.8 lb) 147 kg (310.8 lb) 148 kg (310.8 lb) 149 kg (310.8 lb) 159 kg (310.8 lb) 160 kg (310.8 lb) 170 kg (310.8
(w x d x h) Weight What's in the box Environmental ranges	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, spindle adapter kit (so Operating temperature Storage temperature Operating humidity	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 19 roduction Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F)
(w x d x h)  Weight  What's in the box  Environmental	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 140 cut of Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) <120 watts (printing); < 2 watts (< 7 watts with embedded Digital
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP Designate Universal Print Driver for HP-GL/2 and HP Designate Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 142 cg (310.8 lb) 143 cg (310.8 lb) 144 cg (310.8 lb) 145 cg (310.8 lb) 146 cg (310.8 lb) 147 cg (310.8 lb) 147 cg (310.8 lb) 148 cg (310.8 lb) 149 cg (310.8 lb) 149 cg (310.8 lb) 150 cg (310.
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F)  20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 4.120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/-10%), 50/60 Hz (+/-3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 4.120 watts (printing); 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KC) Compliant with Class A requirements, including: USA (FCC rules), Canada (CCS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety Electromagnetic	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 141 kg (310.8 lb) 142 cy 143 cy 144 cy 145 c
(w x d x h)  Weight  What's in the box  Environmental ranges  Acoustic	Printer Shipping Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety	driver, HP Embedded Web Server, direct printing from USB flash drive, email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)  -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 4.120 watts (printing); 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KC) Compliant with Class A requirements, including: USA (FCC rules), Canada (CCS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China

# **Ordering information**

Product	B9E24A	HP DesignJet T3500 36-in Production Multifunction Printer <sup>9</sup>
	B9E24B	HP DesignJet T3500 36-in Production Multifunction Printer <sup>10</sup>
Accessories	C0C66A	HP DesignJet PostScript/PDF Upgrade Kit
	G8B09A	HP DesignJet T3500 36-in Spindle
	L3J69AAE	HP SmartStream Preflight Manager
	L3J71AAE	HP SmartStream Preflight Manager One-Year Subscription
	L3J78AAE	HP SmartStream Print Controller for HP DesignJet T3500 Production Multifunction Printer
Original HP printheads	B3P06A	HP 727 DesignJet Printhead
Original HP	C1Q13A	HP 764 300-ml Cyan DesignJet Ink Cartridge
ink cartridges	C1Q14A	HP 764 300-ml Magenta DesignJet Ink Cartridge
	C1Q15A	HP 764 300-ml Yellow DesignJet Ink Cartridge
	C1Q16A	HP 764 300-ml Matte Black DesignJet Ink Cartridge
	C1Q17A	HP 764 300-ml Photo Black DesignJet Ink Cartridge
	C1Q18A	HP 764 300-ml Gray DesignJet Ink Cartridge
Original HP large format printing	C6810A	HP Bright White Inkjet Paper (FSC® certified) <sup>11</sup> 🛟 12 914 mm x 91.4 m (36 in x 300 ft)
materials	C6980A	HP Coated Paper (PEFC™ certified)¹¹ 🛟¹² 914 mm x 91.4 m (36 in x 300 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) <sup>11</sup> 🛟 <sup>12</sup> 914 mm x 30.5 m (36 in x 100 ft)
	Q1421B	HP Universal Satin Photo Paper 914 mm x 30.5 m (36 in x 100 ft)

### Service and support<sup>13</sup>

H4518E	HP Installation Service with Network Setup
U1ZX9E	HP 3 year Next Business Day Onsite Support with DMR <sup>14</sup>
U1ZY0E	HP 5 year Next Business Day Onsite Support with DMR <sup>14</sup>
U1ZY1PE	HP 1 year Post Warranty, Next Business Day Onsite Support with DMR <sup>14</sup>
U1ZY2PE	HP 2 year Post Warranty, Next Business Day Onsite Support with DMR <sup>14</sup>
U1XV4E	HP Preventive Maintenance Service

HP DesignJet Support Services offer solutions for business critical environments – installation, extended support and maintenance, as well as variety of value-added services. For more information, please visit hp.com/go/Designjet/support.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays. 15 For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

Choose from a range of third-party solutions like OpCenter and SCP to streamline your digital printing and scanning operations.

- Compared with large-format color MFPs under \$25,000 USD. Based on the fastest-rated color speeds as published by manufacturers as of January 2014. Test methods vary
- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per
- Using HP SmartStream software, job preparation and processing can be completed in 50% of the time. Conclusion based on an HP internal test measuring the time required to extract pages from a 50-page document and print them using several printers compared with using equivalent software programs.
- Available when using HP SmartStream for DesignJet printers together with the HP DesignJet T3500 Production Multifunction Printer
- Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original
- 6 +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP inks.
- Measured on HP Matte Film.
- <sup>8</sup> Based on 2.5 GB RAM.
- 90-day limited hardware warranty.
- <sup>10</sup> One-year limited hardware warranty.
- BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. BMG trademark license code PEFC™/29-31-261, see pefc.org. HP trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.
- 12 Can be recycled through commonly available recycling programs.
- <sup>13</sup> HP Service portfolio available only for B9E24B HP DesignJet T3500 36-in Production Multifunction
- <sup>14</sup> Defective Media Retention keeps your sensitive data safe. To comply with security regulations you can keep the defective hard-drive or data-retentive memory component while getting a new replacement disk or memory.
- <sup>15</sup> True neutral grays produced by printers compatible with the HP Three-black ink set.

















# hp.com/go/designjetT3500



