



HR22 Dorada

Handheld Barcode Scanner



Features

◆ Cost-effective solution.

The HR22 Dorada is specifically developed to provide a cost-effective data capture solution that allows customers to enjoy the capabilities of a 2D scanner for the price of a 1D scanner. This without making any compromises on scan performance, ergonomics or design.

◆ Elegant appearance.

Blending ergonomics and aesthetics in its design, the HR22 Dorada ensures operator comfort and productivity for intensive hand-held scanning. The scanner is ideally suited for applications at the point-of-sale and O2O (Online2Offline).

◆ Durable construction.

The HR22 Dorada has an IP42 rating and is drop resistant up to 1.5m. Its durable housing guarantees optimal protection.

◆ Outstanding performance.

Equipped with Newland's third-generation decoder chip, the HR22 Dorada can effortlessly capture high-density, high-volume and distorted barcodes printed on paper or displayed on screen / mobile phones.

◆ Stand as an accessory.



Application Scenarios

Point of Sale / retail, product traceability, track & trace, healthcare, inventory management, ticket / voucher management and general office automation.

HR22 Dorada

Handheld Barcode Scanner

Performance	Image Sensor	640×480 CMOS		
	Symbologies	2D	PDF417, QR Code (QR1/2, Micro), Data Matrix (ECC200, ECC000,050, 080, 100, 140)	
		1D	Code128, UCC/EAN-128, AIM-128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, GS1-DataBar™(RSS), (RSS-14, RSS-Limited, RSS-Expand)	
	Resolution	≥3mil		
	Typical Depth of Field	EAN-13	35mm-360mm(13mil)	
		Code 39	20mm-160mm(5mil)	
		PDF 417	20mm-110mm (6.67mil)	
		Data Matrix	15mm-100mm (10mil)	
		QR	15mm-150mm(15mil)	
	Scan Angle	Pitch	±60°@ 0°Roll and 0° Skew	
Roll		360°@ 0°Pitch and 0° Skew		
Skew		±55°@ 0°Roll and 0° Pitch		
Min. Symbol Contrast	30%			
Interfaces	RS-232, USB			
Physical	Dimensions (L×W×H)	145×101×68mm		
	Weight	165g		
	Notification	Beep, LED indicator		
	Power Adaptor (optional)	Output: DC 5V, 1.5A Input: AC 100~240V, 50~60Hz		
	Current	Maximum	<270mA	
		Operating	240mA	
		Standby	10mA	
Environmental	Operating Temperature	-20°C~55°C		
	Storage Temperature	-40°C~70°C		
	Humidity	5%~95% (non-condensing)		
	ESD	±8 KV (contact discharge); ±15 KV (air discharge)		
	Drop	1.5m		
	Sealing	IP42		
Certifications	FCC Part15 Class B , CE EMC Class B			

Specifications are subject to change without notice.

Version: V1.0

Newland EMEA HQ
+31 (0) 345 87 00 33
info@newland-id.com

Newland D-A-CH
+49 (0) 6182 82916-16
info@newland-id.de

Newland France
+31 (0) 345 87 00 33
france@newland-id.com

Newland Benelux
+31 (0) 345 87 00 33
benelux@newland-id.com

Newland Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Newland Italy
+39 (0) 342 056 2227
italy@newland-id.com

Newland Nordic & Baltic
+46 (0) 708 847 767
nordic@newland-id.com

Newland UK
+44 (0) 1442 212 020
sales@newland-id.co.uk

Newland Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Newland South Africa
+27 (0) 11 553 8010
info@newland-id.co.za

Newland Middle East
+31 (0) 345 87 00 33
middleeast@newland-id.com

Newland Turkey & Iran
+90 (0) 544 538 40 49
turkey@newland-id.com
iran@newland-id.com