



# High Quality, Reliability, and Convenience

IDP WISE-CXD80 the printer delivers the maximum impact and ease-of-use with glossy photo, real edge-to-edge printing, remains free of head-damage and offers real versatility all with a dramatically smaller body design.

Ideal for both simpler applications such as single-side membership cards, gift cards, on demand ID cards and for corporate and governmental ID card, the WISE-CXD80 provides the integration of proven, long-established technology with a compact and user-friendly body.

- · Color & Mono Single or Dual Sided Printing
- Print Speed: 29 sec./card (YMCK)
- · Detachable and anytime-refillable hopper
- · Intuitive and flexible function LCD panel
- Removable and water-washable cleaning roller
- · Security locks on hopper & front door
- · Kensington lock
- · Inline encoding and lamination (with optional unit)
- · Environmentally friendly compact design











- · Dye Diffusion UV Printing
- · Security Erase Function for K panel
- IP Sec Protocol Security



## SMALL, LIGHT and Compact Body

- Stress-free installation for office, Kiosk and facility use
- Advanced Carrying Portability for big and/or governmental application
- All option units incl. RFID encoder can be stored inside









# WiSE-CXD80S/CXD80D

## **Specifications**

#### PRINTING

Print Area
Full Bleed (Real Edge to Edge)

Resolution 300dpiDual Sided Printing WISE-CXD80D

#### CARD

Card Feeding Automatic

Card Size ISO CR80 (54mm x 86mm / 2.12"x 3.38")
Card Thickness 0.25mm (10mil) ~ 1,0mm (40mil)

Card Type
PVC, PET, Composite PVC

#### PRINT SPEED

YMCK
YMCKK
29 sec\_/card (124 cards/hour)
YMCKK
40 sec\_/card (90 cards/hour)

## CAPACITY

(WISE-CXD80D)

Input Hopper
Output Hopper
100 cards (0,76mm)
100 cards (0,76mm)

### **SYSTEM**

Display LCDControl Panel 3 Buttons

WIndows Server 2003 R2 SP2, Server 2008

Communication
USB, Ethernet fitted as standard

Power Supply
Max. 3A (100V to 120V) | Max. 1.5A (220V to 240V)

• Temperature  $15~35\,^{\circ}$ C • Humidity 35~70%

#### DIMENSIONS

Millimeter (WxLxH) 343 x 322 x 335
Inch (WxLxH) 13.5 x 12.7 x 13.2

#### WEIGHT

• Kg/lbs CXD80S: 13.0 / 28.7 | CXD80D: 15.5 / 34.2 (without optional unit)

#### OPTIONS

• Magnetic stripe Encoding (HiCo/LoCo)

- Contact chip Encoding (Read/Write
- · Contactless Encoding
- Bend Remedy Unit, Lamination Unit (WISE-CL600)

#### CERTIFICATIONS

CEFC & WLISTED

#### Consumables



#### YMCK Pack

Full Color Inc Ribbon & Retransfer Film Package

Capacity: Each 1,000 images/roll

#### YMCKK Pack

Full Color Inc Ribbon with Black for Back Side

- Capacity: 750 images/roll

#### YMCKUv

Full Color Inc Ribbon with UV Panel

- Capacity: 750 images/roll

## YMCKPo Pack

Full Color Inc Ribbon with Peel off Panel & Retransfer Film Package

age

Capacity: - Capacity: Each 750 images/roll 1000 images/roll

## CPF 1.0

Clear 1.0mil Patch Film

Capacity: 600 images/roll

## CPS 1.0 A Type

Clear 1.0mil Patch Film with Smart card cut A type

- Capacity: 600 images/roll

## CPS 1.0 B Type

Clear 1.0mil Patch Film with Smart card cut B type

- Capacity: 600 images/roll

## HOF 1.0

Hologram Standard Overlay Film

- Capacity: 1000 images/roll

#### Cleaning Card

Long sleeve cleaning card kit for automatic cleaning

- Capacity: 10 pcs

## Head Cleaning Card

FILM

Retransfer Film Package

Cleaning card kit for manual cleaning

- Capacity: 10 pcs

# **Wise** Series

WISE-CXD80 Retransfer Card Printer is the culmination of the technological development and is the most innovative card printer available for all types of card-issuing applications.

At the cutting edge of retransfer technology, it provides the finest and the most reliable results with a compact body.

#### **WISE** Laminating ID CARD PRINTER



WISE-CL600 Laminator WISE-CXD80 Printer

## Dimension



Specifications and availability may change without notice.





Tel: (66) 0-2322-9535, 0-2722-4040 Fax: (66) 0-2322-7990

www.cps.co.th | www.labeldd.com

f www.facebook.com/cps.co.th

