

iMin M2 Series

Mobile POS

The iMin M2 series comes with more functions to power your business. Use it independently to manage your reservations, table bookings, print orders, QR scanning and more.





Secure your next sale with iMin M2 series.

Streamlined for maximum efficiency and high functionality in one compact device.



Display

Multi-point capacitive touch panel which works effectively even on the smaller screen size



Chargeable

Compatible with charging base



Printer

Built-in 58mm Japan Seiko High Speed Printer works quickly and precisely











Specification

Processor	M2-202: Quad-Core ARM Cortex-A35 1.3GHz	Memory	1GB RAM + 8GB ROM
	M2-203: Quad-Core ARM Cortex-A53 1.3GHz		2GB RAM + 16GB ROM
	M2 Pro: Octa-Core 1.8GHz, Dual*A75 and Hexa*A55		2GB RAM + 16GB ROM (NFC)
Operating System	M2-202 / M2-203: Android 8.1 iMin UI,	Display	5.5" 720 x 1280
	M2 Pro: Android 11 series iMin UI		
Touch Panel	Multi-point Capacitive Touch Panel	Power Adapter	Input: 100 ~ 240V; Output: 5V / 2A
Connectivity	Bluetooth 4.2+,	Wi-Fi	M2-202: 802.11 b/g/n 2.4GHz
	M2-203 / M2 Pro: GPS/GSM/4G LTE, NFC (Optional)		M2-203: 802.11 a/b/g/n 2.4GHz/5GHz
			M2 Pro: 802.11 a/b/g/n ac 2.4GHz/5GHz
Camera	5.0M AF, Support 1D / 2D Barcode Scanning	Battery	7.4V / 2600mAh
Button	Power key, Vol +/- Key	Speaker	1.5W Mono
Printer	High speed printing, up to 100mm/s,	Peripheral Ports	USB Type-C x 1(Support OTG),
	58mmmm in width & 40mm in diameter		3.5mm Audio Jack x 1, Micro SIM x 1,
			TF Card x 1 (Up to 64GB), POGO PIN (6 PIN)
Certification	FCC CE IMDA	Dimensions	207.5 x 82 x 30.5mm
Weight	435g		





^{*}The product pictures and display contents in the above pages are for illustration purposes only. The actual product effects (including but not limited to appearance, color, size) and screen display contents (including but not limited to background UI pictures) might differ.

^{*}The performance results are obtained from iMin's internal laboratory and extracted from specific test environments. In actual use, there might be a difference in performance due to individual differences in product, software, use conditions and environmental factors.