

CVTE I Enterprise Service Group

Mirroring Box

Upgrade Conventional Meeting Room

No wires needed .With one MAXHUB mirroring box, you can cast screens of mobile devices onto displays* including projectors, televisions and fine pitch LED.



> Realtime Wireless Mirroring

No wires needed, only one click*, mirror your devices within 0.09s.*

> 4-Split Screen Mirroring

Allow 4 devices cast screens simultaneously.

> Stream to Multiple Displays

Support casting to 2 displays simultaneously from a single device.

> **Excellent Product Performance**

Android 7.1 OS Support 2.4G/5GHz Dual Frequency Wi-Fi

Vivid Display & Smooth Video Play >

4K UHD Output 60fps Display



Windows 7, MacOS 10.10 or above; mobile phone and tablet: Android 5.0, IOS 9.0 or above e click mirroring function. Otherwise you can use mirroring accessories like MAXHIIR mirroring time. on system requirements are as follows, PC: Windows 7, MacOS 10.10 or above: mobile priorie with MacOS 10.10 solution MAXHUB Assistant is needed for one click mirroring function. Otherwise you can use mirroring accessories like MAXHUB mirroring h would require device pairing for the first time. Aded for mirroring is collected form a non-interference experiment in MAXHUB lab, using MacDook Air (system 10.11, 11 inches) and itandard interactive flat panel (55 inches, resolution 1366*768).

Product Specification

	Main Features
Output Resolution	Support 4K@60fps and above video output when casting onto 1 display Support 2K@60fps and above video output when casting onto 2 displays
Video Encode/Decode	H.264,H.265 hard decoding
Wireless Transmission Protocol	IEEE 802.11 a/g/n/ac
Wireless Band	2.4GHz,5GHz (support transmitting AP hotspot)
Ideal Transmission Distance	30 meters
Wi-Fi Antenna	Support 2T2R
Cable Network	Supported
Compatible Transmit Terminals	Support SM01 wireless mirroring (Windows, Mac OS); support mobile phone/tablet wireless mirroring(Android/iOS)
Transmit Terminal Quantity Limit	8
Screen Split Limit	4
	Operating System
Version	Android 7.1
CPU	2×A72+4×A53
GPU	Mali T860
RAM	4GB
ROM	16GB
	Input/Output
LINE OUT	1
Optical Fiber Output	1
USB2.0	2
HDMI OUT	2
DC Input	1
LAN	1
Security Key Lock	1
Buttons	Short press to freeze/wake, long press to power on/off
LED Indicator	White
	Physical Specification
Product Size (H × W × D)	182×181×31mm
Net Weight	0.35kg
Frame Color	Black
	Electrical Parameter
Powering	Powered by DC 12V
Adapter AC In	220V
Adapter DC Out	12V 1.5A
Constant Running	7×24h
	Environment Requirements
Working Temperature	-5C~40C
Working Humidity	10%~90%RH
Operating Temperature	-20C~60C
Operating Humidity	10%~90%RH
Altitude	5000 meters and below

*Data collected from MAXHUB lab.



244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990 www.cps.co.th • www.facebook.com/cps.co.th

