

MINDEO

LASER SCANNER

MINDEO MD Series

is an auto-trigger, single line laser bar code scanner designed for decoding all standard 1D bar codes. MD Series can easily target the desired bar code and complete the data transmission accurately.

OVERVIEW

MINDEO MD Series is an auto-trigger, single line laser bar code scanner designed for decoding all standard 1D bar codes. With the State-of-art scanning technology embedded inside, the MD Series has a longer working range and wider scan field than a typical CCD scanner.

Standard features like Auto-trigger scanning mode which scanner will automatically convert to auto-scanning mode when place on the auto-scanning stand without further programming setting, furthermore it gives you the user-replaceable cable to host and user friendly programming manual.



APPLICATION

POS Retail Management System
Manufacturing
Automotive Industry
Chemical Industry
Pharmaceutical Industry
Textile Industry
Electronics Industry
Telecommunication
Transportation and Logistics
Health-care Industry
Utilities Application
Government Application

FEATURES

Auto-scanning mode
User-replaceable, single cable to host
Firmware updates via Flash ROM
Easy to program using the programming manual
Futuristic design, certainly catches your attention
Fast scanning speed and wider scanning field
Dust proof
Drop proof - Multiple 4.0 meters drops to concrete

MINDEO MD Series plus specifications

	MD-2250+	MD-2250AT+	MD-2230+	MD-2230AT+
Laser	650nm laser diode			
Scanning Rate	100 scans / sec			
Auto scanning	Non	With stand	Non	With stand
Scanning angle	±60°, ±65°, ±42° (Skew, Pitch, Roll)			
Min. element width	0.127mm (5mil)		0.076mm (3mil)	
Decode capability	UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Codabar(NW7), Code 128, Code 93, Code 11(USD-8), MSI/Plessey, UK/Plessey, UCC/EAN 128, China Post, China Finance, GS1 DataBar (formerly RSS) variants			
Input voltage	5 VDC ± 0.25V			
Power	500 mW (Operating); 950 mW (Max.)			
Current	100 mA (Operating); 190 mA (Max.)			
Standby current	<250uA			
Indicator	Beeper, LED			
Interface supported	Keyboard wedge, RS-232, USB Keyboard, USB virtual COM			
Operating mode	Hand-held, Auto-detection (Optional)			
Dimensions	Height × Width × Depth : 9.5cm × 6.7cm × 15.4cm			
Weight	168g, without cable			
Cable	Straight 2.0m			
Connector type	RJ-45 phone jack connector			
Case material	ABS + PC			
Temperature	0° to 50°C (32° to 120°F), Operating; -40° to 60°C (-40° to 140°F), Storage			
Humidity	5% to 95% (non-condensing)			
Programming method	Manual (reading special barcode)			
Program upgrade	Online			
Decoding depth	5 mil: 40-110mm 10 mil: 10-280mm 13 mil: 15-315mm 16 mil: 25-385mm 35 mil: 145-630mm		3 mil: 5-50mm 10 mil: 10-85mm 13 mil: 10-150mm 16 mil: 25-165mm 35 mil: 145-295mm	
Safety	Laser safety: EN60825-1, Class 1			
	EMC: EN 55022, EN 55024			
	Electrical safety: EN 60950-1			
	Drop resistance: Multiple 4.0m (13.1 ft) drops to concrete			
	Protection class: IP50			

Distributed by :



**Computer Peripheral
and Supplies Ltd.**



244 Soi Pattanakarn 53, Suanluang, Suanluang, Bangkok 10250 Thailand
Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990
www.cps.co.th

MINDEO