

SAP

LINUX

ORACLE

WINDOWS

PRINTRONIX®

LINE MATRIX PRINTERS

# P8000 OpenPrint HD



## OpenPrint™

The World's Only Postscript® and PDF® Line Matrix Printer



Lowest Cost  
of Printing



Unmatched  
Reliability



Most Sustainable  
Print Technology



Direct ERP  
Connection

# OpenPrint HD: P8000 Line Matrix printers with higher resolution and native PDF & PostScript support

Simplicity of PDF & PostScript printing combined with the reliability and low operating cost that only Line Matrix can deliver.

Businesses running enterprise software applications such as ORACLE®, SAP®, LINUX® and WINDOWS® deserve the option of selecting an industrial strength printing solution. OpenPrint™, the Printronix series of Line Matrix printers with higher resolution capability and exclusive firmware architecture, enables ease of connectivity to modern ERP and WMS platforms.

## The Only Printing System Designed To Stand Up To The Rigors Of Industrial Environments

Thanks to OpenPrint, the industrial strength benefits of Line Matrix printing are no longer limited to legacy system environments. Native Ghostscript PostScript and PDF support allow for high quality printing of PostScript & PDF output containing text, graphics and barcodes.

**Unlock the advantages of Line Matrix technology for your enterprise printing needs.**



## The Printronix Challenge: Can Your Printer Do This?

- ▶ **Consumables that are up to six times less expensive than laser printers**
- ▶ **Non-stop performance in industrial environments: extreme hot or cold, humidity, dust or airborne contaminants**
- ▶ **Jam-free operation for demanding business forms and high volume printing**
- ▶ **High-quality text and graphics without the need for custom coding**



# OpenPrint HD: Higher-definition Line Matrix printers for PDF and PostScript printing



**Open Pedestal** for easy forms access with a small, maneuverable footprint.



**Quiet Cabinet** for large, unattended and secure print jobs.



**Zero Tear** for on-demand printing without forms waste.

**Only Line Matrix offers proven high reliability, uptime performance and environmental responsibility. All delivered by the power of OpenPrint from Printronix.**



- **GRAPHICS** = Prints graphics easily and with clarity. Forms can be designed and printed with enhancements such as non-grayscale logos, illustrations and graphics.
- **BAR CODES** = Printronix Sure Scan technology replaces embedded barcodes with printer generated barcodes for optimal readability.
- **NO CODING REQUIRED** = Designing and modifying business forms is quick and easy. Use any GUI form design program. Even Microsoft Word!
- **FONTS** = Prints the full range of fonts and sizes, from 6 point to poster size. Any font that is embedded into your file, whether PostScript or PDF, will reproduce with ease.



**MOST SUSTAINABLE PRINT TECHNOLOGY** Printronix Line Matrix printers last years longer, consume less electricity and generate far less consumables waste. In addition, Printronix smart cartridge ribbons are manufactured with 100% recycled plastic resin.

# OpenPrint HD Technical Specifications

## PRINTER MODELS

OpenPrint™ P8ZPH (Zero-Tear)  
OpenPrint™ P8PPH (Open Pedestal)  
OpenPrint™ P8CPH (Cabinet)

## PRINT SPEED – IPM (INCHES PER MINUTE\*)

|           | P8CPH | P8ZPH / P8PPH |
|-----------|-------|---------------|
| 180 x 180 | 79    | 64            |
| 120 x 120 | 165   | 133           |
| 90 x 180  | 147   | 119           |
| 180 x 90  | 147   | 119           |
| 90 x 90   | 236   | 191           |

\*Specification is based on 25% vertical image density, meaning print image exists on 25% of the available vertical dot rows. If the vertical coverage is higher or lower, the speed will decrease or increase proportionally. The width of the image has no effect on the print speed. The highest resolution is typically used with high density barcode applications. OpenPrint™ has the ability to speed up when lower resolutions are used.

## GRAPHICS RESOLUTION

|         |   |
|---------|---|
| 180x180 | sure scan enabled (horizontal and vertical bar codes) |
| 120x120 | sure scan enabled (horizontal and vertical bar codes) |
| 90x180  | sure scan enabled (vertical bar codes only)           |
| 180x90  | sure scan enabled (horizontal barcodes only)          |
| 90x90   | sure scan disabled**                                  |

\*\*sure scan bar code optimization is enabled by default for resolutions of 120 DPI and higher. It is disabled for goxgo.

## DOT SIZE

9 mil (0.23mm)

## EMULATIONS

Ghostscript Postscript (Level 3 compatible) and PDF (Level 1.7 compatible)  
Printronix P.JL is also included for job control and configuration  
Artifex, the Artifex logo, Ghostscript, and the Ghostscript logo are registered trademarks of Artifex Software, Inc. Postscript is a trademark of Adobe Systems Incorporated.

## COMMUNICATION INTERFACE

Standard: Serial RS-232, USB 2.0, Ethernet 10/100 BaseT  
Optional: Parallel IEEE-1284, Centronics

## FONTS

35 Standard Postscript Level 3 fonts: Bookman-Demi, Bookman-Demitalic, Bookman-Light, Bookman-Lightitalic, Courier, Courier-Oblique, Courier-Bold, Courier-BoldOblique, AvantGarde-Book, AvantGarde-BookOblique, AvantGarde-Demi, AvantGarde-DemiOblique, Helvetica, Helvetica-Oblique, Helvetica-Bold, Helvetica-BoldOblique, Helvetica-Narrow, Helvetica-Narrow-Oblique, Helvetica-Narrow-Bold, Helvetica-Narrow-BoldOblique, Palatino-Roman, Palatino-Italic, Palatino-Bold, Palatino-BoldItalic, NewCenturySchlbk-Roman, NewCenturySchlbk-Italic, NewCenturySchlbk-Bold, NewCenturySchlbk-BoldItalic, Times-Roman, Times-Italic, Times-Bold, Times-BoldItalic, Symbol, ZapfChancery-MediumItalic, ZapfDingbats

## DRIVERS

Windows XP, 8, 10; Windows Server 2012, 2016; Linux/UNIX

## SURE SCAN BAR CODES

EAN 8/13, UPC A/E, EAN/UPC Addon 2 or 5, Code 39, Code 128, UCC/EAN 128, Interleaved 2 of 5, Codabar, Industrial 2 of 5, BCD Matrix, Code 93, Inverted 2 of 5, IATA 2 of 5, Matrix 2 of 5, Datalogic 2 of 5

**PRINTRONIX**  
WHEN RELIABILITY COUNTS

PTX-30043A



## ORACLE CONNECTIVITY

Use Windows or Linux driver as required.

## SAP CONNECTIVITY

SAPscript: Use Generic POST2 driver resident with SAP  
SmartForms: Use Generic POST2 driver resident with SAP  
Interactive Forms: Direct PostScript supported

To learn more about our SAP Vendor Alliance, visit: [printronix.com/solutions/sap-integration](http://printronix.com/solutions/sap-integration)

## POWER CONSUMPTION

|       |                                |
|-------|--------------------------------|
| P8ZPH | 475 Watts Printing, 5W Standby |
| P8PPH | 475 Watts Printing, 5W Standby |
| P8CPH | 475 Watts Printing, 5W Standby |

## OPERATING ENVIRONMENT

Operating Temperature: 50° to 104° F, 10° to 40° C  
Power Voltage: Line Auto Ranging 100-120 VAC, 200-240 VAC, 50/60 Hz (+/-10%)  
Acoustic Noise: 55dB - P8CPH, 65dB - P8PPH, 68dB - P8ZPH  
Environmental Advantage: Improved handling of recycled paper, faster power-up from sleep mode than laser printers

## MEDIA SPECIFICATIONS

Form Thickness: Maximum 0.025" (0.64mm)  
Form Length: 3" (76mm) to 12" (305mm) maximum  
Form Copies: Up to 4 part  
Form Width: 3" (76mm) to 17" (432mm) maximum  
For Zero Tear models: 7.5" (191mm) to 16" (406mm) for up to 4 part carbonless.  
Form Weight: 15 lb. bond to 100 lb. Tag  
For Zero Tear models: 18 lb. bond to 100 lb. Tag 67.7 to 163 gm/M2 for forms up to 12" (305mm) in width.  
20 lb. bond to 100 lb. Tag 75.2 to 163 gm/M2 for forms up to 16" (406mm) in width.

## FORMS HANDLING

Type: Continuous, fan folded, edge-perforation  
Paper Path: Straight through paper path with easy-load twin adjustable tractors  
Feed: Bottom feed  
Forms: Paper-out detector/alarm, paper motion detector/alarm  
Print Width: 13.6" (345mm)

## MEAN TIME BETWEEN FAILURE

10,000 hours

## GENUINE PRINTRONIX CARTRIDGE RIBBONS

Extended Life HD Cartridge Ribbon: 34,000 pages  
Estimated page yield based on ISO LSA page, 8.5"x11" letter size, approximately 5% coverage



LINE @cps.co.th



Computer Peripheral  
and Supplies Ltd.

244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand  
Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990  
[www.cps.co.th](http://www.cps.co.th) • [www.facebook.com/cps.co.th](https://www.facebook.com/cps.co.th)