



**Computer Peripheral  
and Supplies Ltd.**

244 Soi Pattanakarn 53, Suanluang, Suanluang, Bangkok 10250 Thailand  
Tel : (66) 0-2322-9535, 0-2722-4040 Fax : (66) 0-2322-7990  
www.cps.co.th • www.facebook.com/cps.co.th



## Quotation Sheet of Portable Printer

<b>Item Name:</b>	2" Thermal Portable Printer
<b>Item #:</b>	RPP-02
<b>Product Photo:</b>	
<b>Price(FOB):</b>	
<b>Printing way:</b>	Thermal sensitive line dot method
<b>Paper width:</b>	56mm
<b>Paper thickness:</b>	60 ~ 80µm
<b>Valid printing width:</b>	48 mm
<b>Resolution:</b>	8 dot/mm (230 dpi)
<b>Dot /line:</b>	384 dots
<b>Printing speed:</b>	50-80 mm/s
<b>Printing content:</b>	Support any language
<b>Outer dimension:</b>	102*108*50mm
<b>Weight:</b>	340g
<b>Rolling paper Diameter:</b>	≤30.5mm
<b>Interface:</b>	Original IR( RAW_IR), VIR, IrDA ( IrCOMM) RS232 port, blue tooth, interfaces varied with different models.
<b>Environment parameters:</b>	Working temperature: -10°C ~ 50°C Working humidity: 20% ~ 85% Storing temperature : -20°C ~ 70°C Storing humidity: 5% ~ 95%
<b>Paper feeding method:</b>	Easy paper loading
<b>Mark position:</b>	Detecting mark position
<b>Paper sensor:</b>	LED indicator flashes when come to paper end meanwhile alarm.
<b>Printing Command:</b>	ESC/POS compatible with commands set
<b>Power:</b>	1600 mAh rechargeable li-ion battery
<b>Power alarm:</b>	indicator flashes when printer will run out of power and give out two short hoots. When running out of power, buzzle will give out interval warning to indicate charging.